



SGD-300GE

High-end Display Chiller

Product Features

- Great product presentation
- Low energy consumption
- Skinplate exterior/interior
- Ideal for branding
- Reversible glass door
- Adjustable wire shelves
- LED interior light with switch
- Adjustable legs
- Digital controller and temperature display
- Automatic defrost
- Mobile frame available as accessory

Premium low-energy bottle cooler

The SGD bottle cooler is designed for the hospitality sector and is particularly well-suited for events. It has a sophisticated look with an anthracite exterior, a reversible glass door, and bright interior LED lighting which offers superior product presentation.

The reason we say the SGD cooler is well-suited for events is because of how sturdy it is. The refrigerated unit is strategically placed below the display compartment for efficient ventilation and protection of delicate components. To improve mobility, a stainless steel trolley with robust wheels is available as an accessory, ensuring safe and easy relocation during events and shows.

In addition to its robust design, the SGD display cooler excels when it comes to energy efficiency. Its ventilated cooling system is not only effective in holding the correct temperature, but also results in impressively low energy consumption, making it a great choice for businesses looking to reduce their operational costs.

Measures and Content		
Temperature Range	°C	+2 to +12
Climate Class		4
Gross / Net Weight	kg	115 / 107
Gross / Net Volume	l	270 / 260
Design and Material		
Bottom Shelf Dimensions		520 x 369
Door Number & Type		1 hinged glass door
Max load on Shelves	kg/m ²	150
Shelf Color		Chrome
Shelf Dimensions		496 x 341 mm
Shelves Number & Type		4 adjustable
Tempered glass		No
Feet / Legs		Adjustable Feet
Exterior Finish		
Interior Finish		
Interior Light		LED
Lock		Yes
Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant		R290
Refrigerant Charge	g	90
Thermometer		Yes
Power and Consumption		
Input Power	W	280
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	48
Dimensions		
Internal Dimension (WxDxH)	mm	520 x 380 x 1445
External Dimension (WxDxH)	mm	600 x 575 x 1805
Packed Dimension (WxDxH)	mm	1950 x 800 x 575 mm
40ft Container Load	pcs	122

