



## CRPF2424

Chiller Room

### Product Features

- Plug-In - ready after assembly
- Many customisation possibilities
- Easy access to products
- Easy assembly
- Anti-slip floor in SS304 stainless steel
- 80 mm panel insulation
- Shelves available as accessory
- Ramp available as accessory for easy access

Cost-effective, easy and efficient storage through cold r

### Measures and Content

|                    |                |           |
|--------------------|----------------|-----------|
| Wall Thickness     | mm             | 80        |
| Internal Volume    | m <sup>3</sup> | 10.24     |
| Temperature Range  | °C             | 0 to +8   |
| Gross / Net Weight | kg             | 596 / 566 |

### Design and Material

|                    |                                  |      |
|--------------------|----------------------------------|------|
| Door Number & Type | 1 hinged solid door W:700 H:1845 |      |
| No. of Doors       | 1                                |      |
| Max Load on Floor  | kg/m <sup>2</sup>                | 1500 |
| Interior Light     | LED                              |      |
| Lock               | Yes                              |      |
| Exterior Finish    | White                            |      |
| Interior Finish    | White                            |      |

### Cooling and Functions

|                    |                    |     |
|--------------------|--------------------|-----|
| Type of Controller | Electronic         |     |
| Type of Defrost    | Automatic, hot gas |     |
| Refrigerant        | R290               |     |
| Refrigerant Charge | g                  | 170 |
| Thermometer        | Yes                |     |

### Power and Consumption

|                           |          |            |
|---------------------------|----------|------------|
| Annual Energy Consumption | kWh/year | 8541       |
| Energy Consumption        | kWh/24h  | 23.4       |
| Input Power               | W        | 910        |
| Voltage / Frequency       | V/Hz     | 220-240/50 |
| Noise Level               | dB(A)    | 60         |

### Dimensions

|                            |     |                    |
|----------------------------|-----|--------------------|
| External Dimension (WxDxH) | mm  | 2400 x 2400 x 2200 |
| Internal Dimension (WxDxH) | mm  | 2240 x 2240 x 2040 |
| Packed Dimension (WxDxH)   | mm  | 2500 x 1900 x 2400 |
| 40ft Container Load        | pcs | 8                  |



Strong handle



Shelf as accessory

Cold rooms are ideal as a plug-in solution with an easy simple set-up process. The cooling unit arrives completely pre-mounted within a panel and doesn't require additional expert knowledge to assemble, making things easier for you.

The interchangeable modular panels mean you can change the positioning in various ways to suit you, both in terms of the panel and the cooling unit, or moving the panel with the door to a panel of the same size.

Cold rooms work well within restaurant, delis and cafes environments, and similar settings too, providing an easy walk-in storage solution. They are a great way to optimise your space with efficient cooling in a cost-effective way. Cold rooms create a great chilled environment to store foods, beverages and dairy products and are available as both cooler and freezer units on our website. There's also a vast range of sizes to choose from to suit your environment and business needs. You can also add shelves to provide extra storage space, these are optional.

A ramp is also available as an optional extra to provide easy access, by using lightweight trolleys and bakery racks. It's important to note that the cold room range is not suitable for pallet trucks or jacks. The cold room range is also designed for indoor use only.

Our cold room range is also a great way to minimise energy consumption, keeping your costs lower. The energy efficient cooling system combines with the polyurethane insulation in the panels to achieve this.