



SOCA45INTB

Serve Over Counter

Product Features

- · Excellent product visibility
- · Black finish
- Glass front lifts up for easy cleaning
- Temperature Class 3M1
- Ventilated cooling
- Anti mist front glass
- · LED top light
- Stainless steel bumper bars
- · Stainless steel rear shelf
- Can be multiplexed with kit (POA)

45° corner module for serve over counter

This SOCA corner module is designed specifically for creating complete counter solutions, combining with other serve over counters from the same range. If you require a 90° rounded corner, it's also possible to combine two of these 45° corner modules together. This specific model is narrow out towards the customer with the wider area towards the staff side. We also offer a model with the opposite dimensions, depending on the way you'd like your counter to turn. This high-quality serve over counter presents a sleek design featuring anti-mist glass, LED top lighting, as well as a spacious stainless steel deck that stays chilled - thanks to ventilated cooling and airholes on the rear of the deck. It's ideal for both butcher shops and delis looking to create a striking display space. As well as it's aesthetic design, it's practical and easy to clean with a stainless steel interior and front glass that lifts upwards and stays in place during cleaning. Be aware that if the corner module is installed along with another SOC counter, you cannot open the front glass on both units at the same time or you risk ruining the glass.

Measures and Content		
Total Display Area	m²	0.91
Temperature Range	°C	0 to +4
Climate Class		3
Gross / Net Weight	kg	220 / 180
Gross / Net Volume	I	230
Design and Material		
Door Number & Type		
Tempered glass		Yes
Shelves Number & Type		
Feet / Legs		Adjustable Feet
Interior Light		LED
Lock		No
Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Electric
Refrigerant		R290
Refrigerant Charge	g	130
Thermometer		Yes
Power and Consumption		
Max Ambient		25°C at 60% RH
Input Power	W	310
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60
Dimensions		
Internal Dimension (WxDxH)	mm	900 x
External Dimension (WxDxH)	mm	x 1120 x 1190
Packed Dimension (WxDxH)	mm	1500 x 1250 x 1400
40ft Container Load	pcs	8





Digital controller

Bumper bars