



SFI250-CF VS

Supermarket Cooler / Freezer

Product Features

- Easily switchable between cooler and freezer
- Energy saving variable speed compressor
- Excellent product visibility
- Sliding curved lids
- Ideal in combination with our top section MTF
- Adjustable false base
- LED interior light
- Bumper bars
- Union kit for island creation is available as option

Supermarket cooler / freezer with curved glass for full vi

The SFI cooler / freezer is perfect for displaying products in supermarkets, grocery stores, butchers, pet food stores etc. The curved glass sliding lids allow full visibility of the products inside. The energy efficient LED interior lighting on the back wall of the freezer, illuminates the products beautifully. The LED light has its own separate power cord, so it can be connected to the rest of the light in the store and be turned off at night to save energy. The supermarket cooler / freezer can be arranged into islands with a head case on each end or below a MTF top section. The variable speed compressor ensures that the unit only regulates the temperature when needed. This makes it app. 20% more energy efficient compared to the same model without a variable speed compressor – and thereby more cost efficient to operate. The SFI range also comes as a freezer option as well as in several colors - contact our sales team for more information.

Measures and Content

Total Display Area	m ²	1.73
Temperature Range	°C	-24 to -18 / -1 to +8
Climate Class		4
Gross / Net Weight	kg	220 / 201
Gross / Net Volume	l	1104 / 718

Design and Material

Lid No & Type		2 curved sliding glass lids
Basket No & Type		
Divider System		Yes
Number of dividers	pcs	5
Feet / Legs		6 adjustable legs
Exterior Finish		White
Interior Finish		White painted steel
Interior Light		LED Horizontal

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Static
Type of Defrost		Automatic, hot gas
Refrigerant		R290
Refrigerant Charge	g	130
Thermometer		Yes

Power and Consumption


Energy Class		C
Max Ambient		30°C at 55% RH
Energy Consumption	kWh/24h	5.51
Annual Energy Cons.	kWh/year	2011.15
Power		13 Amp
Input Power	W	890
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	48

Dimensions

Internal Dimension (WxDxH)	mm	2370 x 720 x 627
External Dimension (WxDxH)	mm	2506 x 858 x 890
Packed Dimension (WxDxH)	mm	2570 x 915 x 980
40ft Container Load	pcs	16



Digital controller



Adjustable false base