



NIC301SCEB

Ice Cream Freezer

Product Features

- Angled display for better presentation
- Includes full set of baskets
- Curved sliding lids with lock
- Great branding possibilities
- Digital thermometer
- Castors with brake
- Climate class 5 for high performance in warm surroundings

Elegant chest freezer with curved sliding glass lids

The NIC-SCEB range is a compact display chest freezer in an elegant design. It has curved corners, rounded edges and curved sliding glass lids.

It is a very stable and solid build, but at the same time on wheels so that it is easy to change location in the shop.

It comes in many sizes, which makes this model perfect for smaller shops and delis with limited space as well as lager shops, gas stations, supermarkets etc.

All sizes are environmental friendly and can be branded for better presentation of the cabinet content.

The SCEB-range is with a lower front than back and curved sliding glass lids. Both features provides a better visual display and presentation of the content. This makes the freezer ideal for display of frozen food including ice cream and lollies. Temperature can be held around -14°C for ice cream or around -21°C for other frozen foods.

All sizes have glass lids with a lock for security. They also have a defrost drain for cleaning out the unit.

Measures and Content

Gross / Net Weight	kg	70 / 62
Net Volume	l	218
Gross Volume	l	286
Gross / Net Volume	l	286 / 218
Temperature Range	°C	-24 to -14
Climate Class		5

Design and Material

Exterior Finish		White
Interior Finish		White painted steel
Number of lids		2
Lid No & Type		2 curved sliding glass lids
No. of baskets	pcs	4
Basket No & Type		4 Wire baskets, white
Max No. of Baskets	pcs	4
Castors		4 wheels, 2 with brake
Lock		Yes
Tempered glass		Yes

Cooling and Functions

Type of Controller		Mechanical
Type of Cooling		Static
Type of Defrost		Manual
Refrigerant		R290
Refrigerant Charge	g	85
Thermometer		Yes

Power and Consumption

Energy Class		D
Max Ambient		+40°C, 40% RH
Energy Consumption	kWh/24h	1.75
Annual Energy Cons.	kWh/year	638
EEL	%	42.9
Power Supply		13 Amp
Input Power	W	141
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	45

Dimensions

External Dimension (WxDxH)	mm	1030 x 650 x 918
Internal Dimension (WxDxH)	mm	890 x 510 x 571
Packed Dimension (WxDxH)	mm	1100 x 765 x 990
40ft Container Load	pcs	64



Baskets



Lock