TEFCOLD®
COOL PRODUCTS WORLDWIDE



LGF7500

Glass Door Display Freezer

Product Features
- Fully automatic, fan assisted cooling
- Automatic defrost
- Lock
- Adjustable shelves
- Castors and locking feet
- Self closing doors with stay open feature for ease of loading
- LED interior light with switch (2 LED strips per door)
- Digital controller and temperature display
- Light canopy with switch
- Heated glass door to prevent condensation
- Internal stainless steel base

The TEFCOLD LGF range of glass door freezers gives you the option of matching single, double and triple door units (also with matching chiller versions). These robust cabinets come with some great features. Each door has two vertical LED light strips for excellent internal illumination and a large LED light canopy. The base inside the unit is stainless steel for easy cleaning. The carefully designed refrigeration system is energy efficient to keep running costs down. All units come fitted with castors so you can easily move the unit (for cleaning etc), but also with locking feet. All round a versatile quality unit at a great price ideal for frozen foods and ice cream.

Measures and Content		
Gross / Net Weight	kg	255 / 240
Net Volume	l	1436
Gross Volume	l	2050
Gross / Net Volume	l	2050 / 1436
Total Display Area	m²	2.07
Temperature Range	°C	-25 to -14
Climate Class		4
Design and Material		
Exterior Finish		White
Interior Finish		White
No. of Doors		3
Door Number & Type		3 hinged glass doors
No. of Shelves	pcs	15
Shelves Number & Type		15
Shelf Dimensions		618*622 / 690*622
Interior Light		2 x Vertically LED in door frame
Cooling and Functions		
Type of Cooling		Ventilated
Type of Defrost		Automatic, electric
Refrigerant		R290
Refrigerant Charge	g	120
Thermometer		Yes
Power and Consumption		
Energy Class		D
Energy Consumption	kWh/24h	25.57
Annual Energy Consumption	kWh/year	9335
EEI	%	49
Power		13 Amp
Input Power	W	1200
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	75
Dimensions		
External Dimension (WxDxH)	mm	2079 x 805 x 2065
Internal Dimension (WxDxH)	mm	1959 x 640 x 1520
Packed Dimension (WxDxH)	mm	2130 x 860 x 2210
40ft Container Load	pcs	14



Digital controller


Strong castors