




CRPF1821

Coldroom (Cooling)

Product Features

- Plug-In - ready after assembly
- Many customisation possibilities
- Easy access to products
- Easy assembly
- Anti-slip floor in SS304 stainless steel
- 80 mm panel insulation
- Shelves available as accessory
- Ramp available as accessory for easy access

Measures and Content

Internal Volume	m³	6.49
Wall Thickness	mm	80
Insulation Density	kg/m³	42
Temperature Range	°C	0 to +8
Climate Class		5
Gross / Net Weight	kg	485 / 452
Gross / Net Volume	l	

Design and Material

Door Number & Type	1 hinged solid door W:700 H:1845	
Max Load on Floor	kg/m²	1500
Exterior Finish	White	
Interior Finish	White	
Interior Light	LED	
Lock	Yes	

Cooling and Functions

Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic, hot gas	
Refrigerant	R290	
Refrigerant Charge	g	130
Thermometer	Yes	

Power and Consumption

Energy Consumption	kWh/24h	18.72
Annual Energy Consumption	kWh/year	6833
Input Power	W	860
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60

Dimensions

Internal Dimension (WxDxH)	mm	1640 x 1940 x 2040
External Dimension (WxDxH)	mm	1800 x 2100 x 2200
Packed Dimension (WxDxH)	mm	2200 x 1300 x 2400
40ft Container Load	pcs	14



Strong handle



Shelf as accessory