



CRU1520P w/o Panel

Monoblock Cooler Unit (15,1-20m³)

Product Features

- Monoblock cooling unit
- Automatic condensate evaporation
- Ambient temperature up to +43 °C and 65% humidity
- Digital controller and temperature display
- Stainless steel finish
- Fits panels with a thickness of 80-150 mm

Monoblock cooler unit for temperature -2 to +8 °C

Monoblock cooler unit for cold rooms with a volume of 15,1-20m³.

When installing the monoblock, ensure a minimum distance of 30 cm between the condenser fan (or heat exhaust) and the ceiling. Sufficient ventilation at the installation location is recommended.

Measures and Content

Gross / Net Weight	kg	110 / 100
Capacity Cooling Coldroom Units	m³	15,1 - 20
Temperature Range	°C	0 to +8

Design and Material

Exterior Finish	SS430
-----------------	-------

Cooling and Functions

Type of Controller	Electronic	
Type of Defrost	Automatic, hot gas	
Refrigerant	R290	
Refrigerant Charge	g	200
Thermometer	Yes	

Power and Consumption

Energy Consumption	kWh/24h	25.92
Annual Energy Cons.	kWh/year	9461
Input Power	W	1390
Voltage / Frequency	V/Hz	220-240/50

Dimensions

External Dimension (WxDxH)	mm	600 x 960 x 880
Packed Dimension (WxDxH)	mm	790 x 1150 x 1170
40ft Container Load	pcs	60



Monoblock rear – no panel attached



Digital controller