



CK7410X1

Counter Cooler GN1/1

Product Features

- Stainless steel
- Ventilated cooling
- Controller with Bluetooth and NFC connectivity
- HACCP compliant data export
- Automatic defrost
- Self-closing doors
- Adjustable legs

Stainless steel counter cooler with GN1/1 shelves

The CK7410X1 is an energy-efficient counter cooler for professional settings. It has a 54% lower energy consumption compared to the previous CK7410/-SP model.

The CK counter cooler is made for professional kitchens, and it offers an ideal solution for keeping ingredients chilled and within easy reach during service. It is made from durable SS304 stainless steel and features automatic defrost and GN1/1 dimensioned shelves for easy cleaning and smooth workflows. The legs are adjustable so it is possible to adapt the height of the table to your needs.

Its ventilated cooling system keeps contents at a consistent temperature, and the electronic controller makes it easy to adjust the temperature to fit your ingredients. The controller has Bluetooth and NFC-connectivity. This means that you via an app can control the lighting, keep an eye of the temperature of the cabinet, and even export data for easy reporting. The CK counter cooler makes an excellent addition to any professional kitchen.

Measures and Content

Gross / Net Weight	kg	173 / 153
Net Volume	l	393
Gross Volume	l	616
Gross / Net Volume	l	616 / 393
Temperature Range	°C	-2 to +8
Climate Class		5

Design and Material

Exterior Finish		SS304
Interior Finish		SS304
No. of Doors		4
Door No & Type		4 hinged self-closing doors
Door Reversible		No
No. of Shelves	pcs	4
Shelves No & Type		4 wire shelves grey
Shelf Color		Grey
Feet / Legs		6 adjustable legs
Lock		No

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant		R600a
Refrigerant Charge	g	95
Thermometer		Yes

Power and Consumption

Energy Class		A
Energy Consumption	kWh/24h	1.82
Annual Energy Cons.	kWh/year	664
EEl	%	23.8
Input Power	W	300
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	38

Dimensions

External Dimension (WxDxH)	mm	2230 x 700 x 860
Internal Dimension (WxDxH)	mm	1669 x 580 x 564
Packed Dimension (WxDxH)	mm	2260 x 730 x 910
40ft Container Load	pcs	32



Easy access to clean dust filter



Drawers available as separate kit