




## CRNF1515

### Freezer Room

#### Product Features

- Plug-In - ready after assembly
- Many customisation possibilities
- Easy access to products
- Freezing unit
- Easy assembly
- 120 mm panel insulation
- Anti-slip floor in SS304 stainless steel
- Alarm kit as accessory
- Shelves available as accessory
- Ramp available as accessory for easy access

Ideal, cost-effective, efficient storage with the freezer ro

TEFCOLD freezer rooms are a great plug-in solution with speedy and simple assembly. The cooling unit arrives completely pre-mounted on a panel so extra expert knowledge is not required for installation. The interchangeable modular panels allows for various positioning of both the freezing unit and the panel with the door within it depending on exact sizing. The freezer room is ideal for restaurants, deli and café settings as well as similar hospitality environments. Create an optimal efficient cooling space at a very affordable price, with a great range of sizes to suit your premises and those of your customers. These rooms are available in freezer and cooling options and shelving is available as an optional extra. You can also make use of a ramp which you can purchase as an add-on. This provides easy access by using lightweight trolleys and baking racks. Please note the freezer room isn't suitable for pallet trucks or pallet jacks. Both our freezer rooms and cold rooms offer good energy efficiency, reducing energy consumption. This is due to the polyurethane insulation in the panels combined with the energy efficient cooling system that works to minimise energy wastage. The freezer and cold room range are suitable for indoor use only.

| Measures and Content |       |            |
|----------------------|-------|------------|
| Internal Volume      | m³    | 3.11       |
| Wall Thickness       | mm    | 120        |
| Insulation Density   | kg/m³ | 42         |
| Temperature Range    | °C    | -20 to -10 |
| Climate Class        |       | 5          |
| Gross / Net Weight   | kg    | 335 / 305  |
| Gross / Net Volume   | l     |            |

| Design and Material |                                  |      |
|---------------------|----------------------------------|------|
| Door Number & Type  | 1 hinged solid door W:700 H:1765 |      |
| Max Load on Floor   | kg/m²                            | 2000 |
| Exterior Finish     | White                            |      |
| Interior Finish     | White                            |      |
| Interior Light      | LED                              |      |
| Lock                | Yes                              |      |


| Cooling and Functions |                    |     |
|-----------------------|--------------------|-----|
| Type of Controller    | Electronic         |     |
| Type of Cooling       | Ventilated         |     |
| Type of Defrost       | Automatic, hot gas |     |
| Refrigerant           | R290               |     |
| Refrigerant Charge    | g                  | 150 |
| Thermometer           | Yes                |     |

| Power and Consumption     |                |            |
|---------------------------|----------------|------------|
| Max Ambient               | 40°C at 40% RH |            |
| Energy Consumption        | kWh/24h        | 22.49      |
| Annual Energy Consumption | kWh/year       | 8208       |
| Power                     | 13 Amp         |            |
| Input Power               | W              | 1100       |
| Voltage / Frequency       | V/Hz           | 220-240/50 |
| Noise Level               | dB(A)          | 60         |

| Dimensions                 |     |                    |
|----------------------------|-----|--------------------|
| Internal Dimension (WxDxH) | mm  | 1260 x 1260 x 1960 |
| External Dimension (WxDxH) | mm  | 1500 x 1500 x 2200 |
| Packed Dimension (WxDxH)   | mm  | 2200 x 1600 x 2400 |
| 40ft Container Load        | pcs | 12                 |



Strong handle



Shelf as accessory