



Trojan T32 FGD EHA

Remote Multideck - Extended Height

Product Features

- Colour is anthracite RAL7016
- Requires remote refrigeration system (not supplied)
- Horizontal LED lighting
- Frameless glass doors for great product visibility
- Adjustable shelves, max weight 160kg/sq metre
- Shelves can be flat or angled to 7° or 14°
- Solid 40 mm endwalls with mirrored interior
- Digital controller and temperature display
- Can be multiplexed with kit (POA)
- EPOS Ticket strips & shelf risers
- Extraction rate 650w/per metre
- Fully automatic, fan assisted cooling

Remote Multideck - Extended Height

These highly useful remote multidecks, at an extended height, which help to maximise your display space whilst also reducing the impact of both noise and heat. The units are available in 4 sizes. You can multiplex these units with a kit, which allows you to create a larger display size. The large display area creates exceptional product presentation with high-capacity vertical merchandising. For use with a huge variety of chilled products with even temperature distribution across all shelf levels. The LED illumination also enhances the display impact, whilst the energy-efficient operation and modular construction allows for seamless continuous line-ups. Important - this requires an additional remote refrigeration system. 2 year parts warranty only.

Measures and Content

Gross / Net Weight	kg	605 / 560
Gross / Net Volume	l	/
Total Display Area	m ²	4.95
Temperature Range	°C	-1 to +5
Climate Class		3

Design and Material

Exterior Finish		Anthracite RAL7016
Interior Finish		Anthracite RAL7016
No. of Doors		6
Door Number & Type		6 hinged glass door
Door Reversible		No
No. of Shelves	pcs	5
Shelves Number & Type		5 adjustable
Shelf Color		Anthracite
Shelf Dimensions		5 x 450 mm
Tempered glass		Yes

Cooling and Functions

Type of Defrost		Automatic
Refrigerant		R449a
Refrigerant Charge	g	REMOTE

Power and Consumption

Energy Class		D
Max Ambient		+25°C, 60% RH
Energy Consumption	kWh/24h	22.51
Annual Energy Consumption	kWh/year	8216
EEl	%	36.2
Voltage / Frequency	V/Hz	220-240/50

Dimensions

External Dimension (WxDxH)	mm	3125 x 784 x 2236
Internal Dimension (WxDxH)	mm	3125 x 450 x 1738
Packed Dimension (WxDxH)	mm	3350 x 850 x 2390
40ft Container Load	pcs	6



Digital controller



Strong handles