



CRPF2427

Coldroom (Cooling)

Product Features

- Plug-In - ready after assembly
- Many customisation possibilities
- Easy access to products
- Easy assembly
- Anti-slip floor in SS304 stainless steel
- 80 mm panel insulation
- Shelves available as accessory
- Ramp available as accessory for easy access

Measures and Content

| | | |
|--------------------|-------|-----------|
| Internal Volume | m³ | 11.6 |
| Wall Thickness | mm | 80 |
| Insulation Density | kg/m³ | 42 |
| Temperature Range | °C | 0 to +8 |
| Climate Class | | 5 |
| Gross / Net Weight | kg | 666 / 636 |
| Gross / Net Volume | l | |

Design and Material

| | | |
|--------------------|----------------------------------|------|
| Door Number & Type | 1 hinged solid door W:700 H:1845 | |
| Max Load on Floor | kg/m² | 1500 |
| Exterior Finish | White | |
| Interior Finish | White | |
| Interior Light | LED | |
| Lock | Yes | |

Cooling and Functions

| | | |
|--------------------|--------------------|-----|
| Type of Controller | Electronic | |
| Type of Cooling | Ventilated | |
| Type of Defrost | Automatic, hot gas | |
| Refrigerant | R290 | |
| Refrigerant Charge | g | 170 |
| Thermometer | Yes | |

Power and Consumption

| | | |
|---------------------------|----------|------------|
| Energy Consumption | kWh/24h | 23.4 |
| Annual Energy Consumption | kWh/year | 8541 |
| Input Power | W | 910 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 60 |

Dimensions

| | | |
|----------------------------|-----|--------------------|
| Internal Dimension (WxDxH) | mm | 2240 x 2540 x 2040 |
| External Dimension (WxDxH) | mm | 2400 x 2700 x 2200 |
| Packed Dimension (WxDxH) | mm | 2500 x 1900 x 2400 |
| 40ft Container Load | pcs | 8 |



Strong handle



Shelf as accessory