




CRNF2427

Coldroom (Freezing)

Product Features

- Plug-In - ready after assembly
- Many customisation possibilities
- Easy access to products
- Freezing unit
- Easy assembly
- 120 mm panel insulation
- Anti-slip floor in SS304 stainless steel
- Alarm kit as accessory
- Shelves available as accessory
- Ramp available as accessory for easy access

Measures and Content

Internal Volume	m³	10.41
Wall Thickness	mm	120
Insulation Density	kg/m³	42
Temperature Range	°C	-20 to -10
Climate Class		5
Gross / Net Weight	kg	800 / 770
Gross / Net Volume	l	

Design and Material

Door Number & Type	1 hinged solid door W:700 H:1765	
Max Load on Floor	kg/m²	2000
Exterior Finish	White	
Interior Finish	White	
Interior Light	LED	
Lock	Yes	

Cooling and Functions

Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic, hot gas	
Refrigerant	R290	
Refrigerant Charge	g	200
Thermometer	Yes	

Power and Consumption


Energy Consumption	kWh/24h	31.78
Annual Energy Consumption	kWh/year	11598
Input Power	W	1630
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60

Dimensions

Internal Dimension (WxDxH)	mm	2160 x 2460 x 1960
External Dimension (WxDxH)	mm	2400 x 2700 x 2200
Packed Dimension (WxDxH)	mm	2500 x 1900 x 2400
40ft Container Load	pcs	4



Strong handle



Shelf as accessory