



## UD1-22

### GN2/1 Uni-Drawer

#### Product Features

- Easily switchable between cooler and freezer
- Maximized storage space
- Suitable for GN pans (max. depth 150 mm)
- Ventilated cooling for fast pull-down and even temperature
- Automatic defrost
- Maximum load capacity per drawer: 60 kg
- Maximum load capacity of table top: 240 kg

### Uni-drawer for GN2/1 pans

The UD uni-drawer features a smart system that lets you switch between cooling and freezing at the touch of a button. Ideal for compact professional kitchens, each module offers precise temperature control, with settings from -18 to -22°C for freezing or +2 to +8°C for cooling.

The uni-drawer is designed to accommodate GN pans up to 150 mm deep, but it can also be used without gastronorm pans. Its reinforced top plate supports heavy countertop equipment, including deep fryers and ovens, making the most of valuable workspace by creating additional prep space.

With the UD uni-drawer, you get a flexible and robust solution with reliable performance – built to meet the demands of busy professional kitchens.

#### Measures and Content

|                    |    |                       |
|--------------------|----|-----------------------|
| Gross / Net Weight | kg | 82 / 72               |
| Net Volume         | l  | 51                    |
| Gross Volume       | l  | 78                    |
| Gross / Net Volume | l  | 78 / 51               |
| Temperature Range  | °C | +2 to +8 / -18 to -22 |
| Climate Class      |    | 4                     |

#### Design and Material

|                 |     |         |
|-----------------|-----|---------|
| Exterior Finish |     | SS304   |
| Interior Finish |     | SS304   |
| Castors         |     | Castors |
| Lock            |     | No      |
| Drawers         | pcs | 1       |
| Interior Light  |     | No      |

#### Cooling and Functions

|                    |   |                           |
|--------------------|---|---------------------------|
| Type of Cooling    |   | Ventilated                |
| Type of Defrost    |   | Airflow/Electrical heater |
| Refrigerant        |   | R290                      |
| Refrigerant Charge | g | 70                        |

#### Power and Consumption

|                     |          |            |
|---------------------|----------|------------|
| Energy Class        |          | C          |
| Energy Consumption  | kWh/24h  | 3.3        |
| Annual Energy Cons. | kWh/year | 1204.5     |
| EEL                 | %        | 45         |
| Input Power         | W        | 240        |
| Voltage / Frequency | V/Hz     | 220-240/50 |
| Noise Level         | dB(A)    | 42         |

#### Dimensions

|                            |     |                 |
|----------------------------|-----|-----------------|
| External Dimension (WxDxH) | mm  | 905 x 700 x 605 |
| Internal Dimension (WxDxH) | mm  | 675 x 565 x 205 |
| Packed Dimension (WxDxH)   | mm  | 975 x 760 x 700 |
| 40ft Container Load        | pcs | 108             |



From fridge to freeze by the touch of one button



GN2/1 drawer