



## MCX90M

Multideck with shutter

### Product Features

- Ideal for impulse buys and promotions
- Lockable security shutter
- Ventilated cooling
- Adjustable shelves
- Automatic defrost
- Castors with brake
- Digital controller and temperature display
- Ticket strip included

The TEFCOLD MCX Range is an open front stainless steel

The TEFCOLD MCX Range is an open front stainless steel multideck, ideal for grab-and-go and impulse purchases. It can be set to temperature suitable for drink, dairy or fresh meat to suit your requirements. The MCX also benefits from a rigid lockable security shutter to prevent access to product when food is not being served, it is also supplied on lockable castors to allow movement of the cabinet. This allows the unit to be more versatile as to where it can be utilised to maximise sales.

The MCX Range is the perfect solution for a wide range of establishments such as cafeterias, hotels, schools, colleges, and university canteens. It caters to the need for a refrigerated multideck during service while also prioritising product security during non-service periods. This feature becomes especially valuable in environments where customers, staff, or students may still have access to the unit.

### Measures and Content

Total Display Area	m <sup>2</sup>	0.89
Temperature Range	°C	-1 to +5
Climate Class		3
Net Volume	l	370
Gross Volume	l	440
Gross / Net Volume	l	440 / 370
Gross / Net Weight	kg	225 / 160

### Design and Material

Door Number & Type		
No. of Shelves	pcs	4
Shelf Color		Stainless steel
Shelves Number & Type		4 adjustable
Castors		Castors
Interior Light		15 W Neon
Exterior Finish		SS304
Interior Finish		SS304

### Cooling and Functions

Type of Controller		Electronic
Type of Defrost		Automatic
Refrigerant		R290
Refrigerant Charge	g	149
Thermometer		Yes

### Power and Consumption

Energy Class		E
Max Ambient		25°C 60% RH
Annual Energy Consumption	kWh/year	3865
Energy Consumption	kWh/24h	10.59
EEl	%	56
Power		13 Amp
Input Power	W	670
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	56

### Dimensions

External Dimension (WxDxH)	mm	868 x 740 x 1994
Internal Dimension (WxDxH)	mm	806 x 436 x 1250
Packed Dimension (WxDxH)	mm	980 x 790 x 2150
40ft Container Load	pcs	28



Security shutter with lock



Strong castors