



RIC880X1 UK

Roll-In Chiller

Product Features

- Stainless steel exterior and interior
- Suitable for 20-tray trolleys (not included)
- Ventilated cooling
- Digital controller and temperature display
- Automatic defrost
- Climate class 5 for high performance in warm surroundings

Roll-In Chiller for catering settings

The TEFCOLD RIC Roll-in Chiller is tailored for professional kitchens. Its 304-grade stainless steel construction ensures durability, while ventilated cooling keeps your prepared dishes fresh and ready to serve. Designed to accommodate 1 x GN2/1, 1 x 600x400mm or 2 x GN1/1 20-tray trolleys (sold separately), it's perfect for bakeries, events, buffets and catering settings. The refrigerator's robust design ensures it can withstand the rigors of a busy kitchen environment, making it a reliable choice for any professional setting. With its combination of functionality and durability, the TEFCOLD RIC Roll-in Chiller is an indispensable asset for any culinary establishment.

Measures and Content		
Temperature Range	°C	+2 to +10
Climate Class		5
Gross / Net Weight	kg	188 / 155
Gross / Net Volume	I	1005 / 416
Design and Material		
Door Number & Type		1 hinged solid door
Shelves Number & Type		
Exterior Finish		SS304
Interior Finish		SS304
Interior Light		No
Lock	_	Yes
Cooling and Functions		
Type of Cooling		Ventilated
Type of Defrost		Automatic-Off Cycle
Refrigerant		R290
Refrigerant Charge	g	105
9	g	105
Refrigerant Charge	g kWh/24h	4.24
Refrigerant Charge Power and Consumption		
Refrigerant Charge Power and Consumption Energy Consumption	kWh/24h	4.24
Refrigerant Charge Power and Consumption Energy Consumption Annual Energy Consumption	kWh/24h kWh/year	4.24 1547.6
Refrigerant Charge Power and Consumption Energy Consumption Annual Energy Consumption Input Power	kWh/24h kWh/year W	4.24 1547.6 330
Refrigerant Charge Power and Consumption Energy Consumption Annual Energy Consumption Input Power Voltage / Frequency	kWh/24h kWh/year W V/Hz	4.24 1547.6 330 220-240/50
Refrigerant Charge Power and Consumption Energy Consumption Annual Energy Consumption Input Power Voltage / Frequency Noise Level	kWh/24h kWh/year W V/Hz	4.24 1547.6 330 220-240/50
Refrigerant Charge Power and Consumption Energy Consumption Annual Energy Consumption Input Power Voltage / Frequency Noise Level Dimensions	kWh/24h kWh/year W V/Hz dB(A)	4.24 1547.6 330 220-240/50 52
Refrigerant Charge Power and Consumption Energy Consumption Annual Energy Consumption Input Power Voltage / Frequency Noise Level Dimensions Internal Dimension (WxDxH)	kWh/24h kWh/year W V/Hz dB(A)	4.24 1547.6 330 220-240/50 52 720 x 836 x 1810
Refrigerant Charge Power and Consumption Energy Consumption Annual Energy Consumption Input Power Voltage / Frequency Noise Level Dimensions Internal Dimension (WxDxH) External Dimension (WxDxH)	kWh/24h kWh/year W V/Hz dB(A)	4.24 1547.6 330 220-240/50 52 720 x 836 x 1810 880 x 994 x 2201.5





Digital controller

Lock