



TM45C

Minibar

Product Features

- Low energy consumption
- Compressor operated cooling system
- Low noise operation
- Timing function for maximum guest comfort
- SLEEP-mode function for silence period
- FAST-cool function for immediate cooling
- · Adjustable shelves, also in door
- · Reversible solid door
- LED interior light
- Integrated handle
- Lock

Minibar cooler with low energy consumption

The TM-C range of hotel minibars from TEFCOLD provides an innovative alternative to the traditional "absorption" refrigeration systems of many minibars. The TM-C model feature a compressor refrigeration system that significantly reduces consumption while providing faster cooling of produce. The units runs at a quiet 38dB and using smart programming can be set to function during periods of the day when the room is likely to be unoccupied (for example between 11am and 4pm). There is also a one press silent function that will sleep the compressor for 1 hour, and a one press function to run the refrigeration system for 5 hours when it is restocked to pull down temperature of the product inside. This range comes in a number of sizes including a drawer version. They are suitable for hotel rooms and boardrooms

Measures and Content		
Temperature Range	°C	+5 to +10
Climate Class		4
Gross / Net Weight	kg	21 / 20
Gross / Net Volume	T	38 / 34
Design and Material		
Door Number & Type		1 hinged solid door
Door Reversible		Yes
Shelves Number & Type		2
Feet / Legs		Adjustable Feet
Exterior Finish		Black
Interior Finish		White
Interior Light		LED
Lock		Yes
Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Static
Type of Defrost		Automatic
Refrigerant		R600a
Refrigerant Charge	g	26
Thermometer		No
Power and Consumption		
Energy Class		D
Energy Consumption	kWh/24h	0.16
Annual Energy Consumption	kWh/year	57
Power		13 Amp
Max Ambient		30°C at 55% RH
Input Power	W	65
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	38
Dimensions		
Internal Dimension (WxDxH)	mm	310 x 300 x 455
External Dimension (WxDxH)	mm	402 x 500 x 565
Packed Dimension (WxDxH)	mm	450 x 535 x 620
40ft Container Load	pcs	330





Integrated handle

Lock