



LGC2500B

Glass Door Merchandiser

Product Features

- Fully automatic
- Fan assisted cooling
- Automatic defrost
- Lock
- Adjustable shelves
- Castors and locking feet
- LED interior light with switch (2 LED strips per door)
- Digital controller and temperature display
- LED Light canopy with switch
- Internal stainless steel base
- Self closing doors with stay open feature for ease of loading

Elegant display chiller with canopy

The TEFCOLD LGC chiller now available in a sleek black finish. This exciting update allows the unit to seamlessly blend into various retail and catering environments, making it an excellent choice for establishments seeking a sophisticated and high-quality aesthetic. Each door boasts two vertical LED light strips, these draw attention to the product on display giving a striking contrast against the black interior of the cabinet. There is also an LED light canopy which is ideal for branding and advertising. The unit's interior base is manufactured from stainless steel and features curved corners to help with cleaning and hygiene. Additionally, the carefully engineered refrigeration system is highly energy-efficient, minimising operational costs while keeping your products at their optimal temperature. The unit is also fitted with castors, to allow moving for cleaning purposes and other necessary adjustments.

Measures and Content		
Total Display Area	m ²	0.69
Temperature Range	°C	+1 to +8
Climate Class		4
Gross / Net Weight	kg	135 / 115
Gross / Net Volume	l	496 / 405
Design and Material		
Door Number & Type	1 hinged glass door	
Max load on Shelves	kg/m ²	196
Shelf Dimensions	545*622	
Shelves Number & Type	5	
Tempered glass	Yes	
Exterior Finish	Black RAL9005	
Interior Finish	Black	
Interior Light	LED	
Cooling and Functions		
Type of Defrost	Off Cycle	
Refrigerant	R600a	
Refrigerant Charge	g	110
Thermometer	Yes	
Power and Consumption		
Energy Class	B	
Max Ambient	30°C at 55% RH	
Energy Consumption	kWh/24h	3.7
Annual Energy Consumption	kWh/year	1349
EEI	%	19
Input Power	W	280
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	58
Dimensions		
Internal Dimension (WxDxH)	mm	565 x 640 x 1520
External Dimension (WxDxH)	mm	685 x 805 x 2065
Packed Dimension (WxDxH)	mm	745 x 860 x 2260 mm
40ft Container Load	pcs	44



Illuminated canopy



Strong castors