



FSC891H Black

Black 2-door display cooler with canopy

Product Features

- Approx. 58% more energy efficient than previous FSC-range
- LED illuminated canopy
- Internal vertical LED light
- Black interior and exterior
- Adjustable shelves
- Ventilated cooling
- Hinged alu-framed glass doors
- Adjustable feet with rollers to rear
- Digital temperature display

Black 2-door display cooler with canopy

The FSC range is with a an illuminated canopy. The possibility for customized branding is eye-catching and stimulate impulse sales. The unit keeps beverages cold whilst presenting and promoting the products to their best advantage. It has been updated and now uses in average 58% less energy compared to the previous models from the same range. This model is with black exterior and interior. The black exterior finish looks great, the black interior makes the content stand out - especially with LED lights perfectly illuminating the content. It is ideal for high-end cafes, delis and patisseries. It comes with 5 adjustable black wire shelves, 2 self-closing hinged glass doors, 2 vertical full length LED lights inside the door frame and a LED light canopy.

Measures and Content

Temperature Range	°C	+2 to +10
Climate Class		4
Gross / Net Weight	kg	166 / 153
Gross Volume	l	707
Gross / Net Volume	l	707 / 535

Design and Material

Door No & Type	2 hinged self-closing glass doors	
Tempered glass		Yes
Door Reversible		No
Shelves No & Type	5 wire shelves black	
Shelf Color		Black
Shelf Dimensions	794 x 540 mm	
Max load on Shelves	kg/m ²	196
Canopy Type		D-Shape
Feet / Legs	4 adjustable feet	
Castors		4 rollers
Exterior Finish	Black RAL9005	
Interior Finish	Black RAL9005	
Interior Light		LED
Lock		Yes

Cooling and Functions

Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic	
Refrigerant	R290	
Refrigerant Charge	g	115
Thermometer		Yes

Power and Consumption

Energy Class	C	
Max Ambient	30°C at 55% RH	
Energy Consumption	kWh/24h	2.63
Annual Energy Cons.	kWh/year	960
Power	13 Amp	
Input Power	W	410
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	48

Dimensions

Internal Dimension (WxDxH)	mm	810 x 561 x 1556
External Dimension (WxDxH)	mm	890 x 740 x 1990
Packed Dimension (WxDxH)	mm	950 x 840 x 2160
40ft Container Load	pcs	28



Illuminated canopy



Strong handles