TEFCOLD
COOL PRODUCTS WORLDWIDE



IC201SCEB

Ice Cream Freezer

Product Features
- Angled display for better presentation
- Curved sliding lids with lock
- 2 wire baskets, white
- Ideal for branding
- Digital thermometer
- Castors with brake
- Climate class 5 for high performance in warm surroundings

Chest freezer with curved sliding glass lids

The IC-SCEB freezer is a price friendly compact display chest freezer. It is great for start-up companies, season sale etc.
It is very stable and solid build, but at the same time on wheels so that it is easy to change location in the shop.


It comes in varies sizes. The many sizes makes the model perfect for smaller shops and delis with limited space as well as larger shops, gas stations, supermarkets etc.
All sizes are environmental friendly and can be branded for better presentation of the cabinet content.

The SCEB-range is with a lower front than back and curved sliding glass lids. Both features provides a better visual display and presentation of the content. This makes the freezer ideal for display of frozen food including ice cream and lollies.
Temperature can be held around -14°C for ice cream or around -21°C for other frozen foods.

All sizes have glass lids with a lock for security. They also have a defrost drain for cleaning out the unit.

Measures and Content		
Gross / Net Weight	kg	58 / 53
Net Volume	l	157
Gross Volume	l	176
Gross / Net Volume	l	176 / 157
Temperature Range	°C	-24 to -14
Climate Class		5
Design and Material		
Exterior Finish		White
Interior Finish		White painted steel
Number of lids		2
Lid No & Type		2 curved sliding temp. glass lids
No. of baskets	pcs	2
Basket No & Type		2 Wire baskets, white
Max No. of Baskets	pcs	2
Castors		4 wheels, 2 with brake
Lock		Yes
Tempered glass		Yes
Interior Light		No
Cooling and Functions		
Type of Controller		Mechanical
Type of Cooling		Static
Type of Defrost		Manual
Refrigerant		R600a
Refrigerant Charge	g	55
Thermometer		Yes
Power and Consumption		
Energy Class		D
Min. Ambient		+16°C, 80% RH
Max Ambient		+40°C, 40% RH
Energy Consumption	kWh/24h	1.51
Annual Energy Cons.	kWh/year	552
EEI	%	44
Input Power	W	98
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	45
Dimensions		
External Dimension (WxDxH)	mm	720 x 615 x 949
Internal Dimension (WxDxH)	mm	600 x 495 x 710
Packed Dimension (WxDxH)	mm	800 x 750 x 1010
40ft Container Load	pcs	92


Baskets


Lock