



## BA21S

### Back Bar Cooler

#### Product Features

- EU Energy Class A
- Approx. 59% more energy efficient than previous BA-range
- Double glazed tempered glass
- Reversible glass door
- Ventilated cooling for fast pull-down and even temperature
- Easy access electronic thermostat
- Adjustable shelves
- LED interior light
- Lock

### High-quality sliding door backbar with low energy consu

The BA21S Backbar Cooler is a pinnacle of efficiency for your food and hospitality business. With an EU Energy Class A rating, it surpasses its predecessors by approximately 59% in energy efficiency, ensuring cost savings without compromising performance. Equipped with double-glazed tempered glass and self-closing sliding doors, this cooler optimises insulation and reduces energy loss while providing easy access. The ventilated cooling system guarantees swift pull-downs and consistent temperatures, preserving the freshness of your inventory. The adjustable shelves, LED interior lighting, and a secure lock offer convenience, visibility, and security in one versatile unit. With energy-saving features, precision temperature control, and a secure design, this cooler is tailored to meet the demands of busy food and hospitality establishments.

#### Measures and Content

Total Display Area	m <sup>2</sup>	0.54
Temperature Range	°C	+2 to +10
Climate Class		4
Gross / Net Weight	kg	70 / 64
Gross / Net Volume	l	196 / 188

#### Design and Material

Door Number & Type		2 sliding glass doors
Shelf Color		Chrome
Shelf Dimensions		395x328 mm
Shelves Number & Type		4 wire shelves chrome
Tempered glass		Yes
Feet / Legs		4 adjustable feet
Exterior Finish		Black
Interior Finish		Stucco aluminium
Interior Light		LED
Lock		Yes

#### Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant		R600a
Refrigerant Charge	g	70
Thermometer		Yes

#### Power and Consumption

Energy Class		A
Max Ambient		30°C at 55% RH
Energy Consumption	kWh/24h	1.14
Annual Energy Consumption	kWh/year	416
EEl	%	9
Power		13 Amp
Input Power	W	115
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	44

#### Dimensions

Internal Dimension (WxDxH)	mm	810 x 418 x 734
External Dimension (WxDxH)	mm	900 x 515 x 900
Packed Dimension (WxDxH)	mm	985 x 575 x 970 mm
40ft Container Load	pcs	96



Door holder for loading of the cabinet



Electronic thermostat of the cabinet



Gross / Net Weight	kg	/
Gross / Net Volume	l	
Door Number & Type		
Shelves Number & Type		
Internal Dimension (WxDxH)	mm	
External Dimension (WxDxH)	mm	x x
Packed Dimension (WxDxH)	mm	x x



## Product Features

