



FSC1450

Glass Door Merchandiser

Product Features

- Fully automatic
- Fan assisted cooling
- Lock
- Adjustable shelves
- Adjustable feet
- LED interior light with switch
- Thermometer
- LED Light canopy with switch
- Replaceable door gasket

If you need a glass door cooler with more capacity than the FSC1380 then the FSC1450 may be ideal for you. With a capacity of 438 litres, this is a great way to maximise storage and display of produce. Ideal for adding your own branding with an LED light canopy to the top.

Measures and Content

| | | |
|--------------------|----|-----------|
| Temperature Range | °C | +2 to +10 |
| Climate Class | | 4 |
| Gross / Net Weight | kg | 107 / 102 |
| Gross / Net Volume | l | 438 / 374 |

Design and Material

| | | |
|-----------------------|----------------------|-----|
| Door Number & Type | 1 hinged glass door | |
| Tempered glass | Yes | |
| Door Reversible | Yes | |
| Shelves Number & Type | 6 wire shelves white | |
| Shelf Color | White | |
| Shelf Dimensions | 574 x 405 mm | |
| Max load on Shelves | kg/m ² | 196 |
| Canopy Type | D-Shape | |
| Canopy Light | LED Cold White | |
| Feet / Legs | 2 adjustable feet | |
| Castors | 2 rollers | |
| Exterior Finish | White | |
| Interior Finish | White | |
| Interior Light | LED | |
| Lock | Yes | |

Cooling and Functions

| | | |
|--------------------|--------------|----|
| Type of Controller | Mechanical | |
| Type of Cooling | Fan assisted | |
| Type of Defrost | Off Cycle | |
| Refrigerant | R600a | |
| Refrigerant Charge | g | 80 |
| Thermometer | Yes | |

Power and Consumption

| | | |
|---------------------------|----------------|------------|
| Energy Class | F | |
| Max Ambient | 30°C at 55% RH | |
| Energy Consumption | kWh/24h | 3.62 |
| Annual Energy Consumption | kWh/year | 1321 |
| Power | 13 Amp | |
| Input Power | W | 295 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 45 |

Dimensions

| | | |
|----------------------------|-----|------------------|
| Internal Dimension (WxDxH) | mm | 585 x 495 x 1515 |
| External Dimension (WxDxH) | mm | 680 x 655 x 2090 |
| Packed Dimension (WxDxH) | mm | 690 x 755 x 2200 |
| 40ft Container Load | pcs | 51 |



Strong handle

Vertical internal light