



## TM45GC

Minibar

### Product Features

- Compressor operated cooling system
- Great product presentation
- Low energy consumption
- Low noise operation
- Timing function for maximum guest comfort
- SLEEP-mode function for silence period
- FAST-cool function for immediate cooling
- Reversible glass door
- LED interior light
- Integrated handle
- Lock

Minibar featuring a glass door for enhanced product visi

The TM-GC range features compressor-operated minibars with a glass door as a great option for hotels located in warmer climates. This minibar features a cooling system that ensures a lower temperature level and a shorter pull-down time when compared to absorption-operated minibars. It also includes various programming functionalities. For instance, it can be set to run only during specific times when the room is likely to be unoccupied, such as from 9-12 am and 6-9 pm, ensuring complete silence when guests are present. The minibar is equipped with a water-pack that maintains a cold temperature even when it's not running. Additionally, it offers a SLEEP mode for silent operation and a FAST-cool function for quick cooling, making it ideal for guests arriving at non-standard hours. The elegantly discreet black exterior coupled with the glass door allows for excellent product presentation, enticing guests with a visually appealing display of cold beverages and delicious snacks.

### Measures and Content

Temperature Range	°C	+5 to +14
Climate Class		4
Gross / Net Weight	kg	26 / 24
Gross / Net Volume	l	38 / 34

### Design and Material

Door Number & Type		1 hinged glass door
Shelves Number & Type		2
Feet / Legs		Adjustable Feet
Exterior Finish		Black
Interior Finish		White
Interior Light		LED
Lock		Yes

### Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Static
Type of Defrost		Automatic
Refrigerant		R600a
Refrigerant Charge	g	26
Thermometer		No

### Power and Consumption


Energy Class		G
Energy Consumption	kWh/24h	0.35
Annual Energy Consumption	kWh/year	128
EEl	%	165
Power		13 Amp
Input Power	W	65
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	38

### Dimensions

Internal Dimension (WxDxH)	mm	310 x 300 x 455
External Dimension (WxDxH)	mm	402 x 485 x 565
Packed Dimension (WxDxH)	mm	450 x 535 x 620 mm
40ft Container Load	pcs	330



Integrated handle



Display with a button for each feature