



TM35C

Minibar

Product Features

- Low energy consumption
- Compressor operated cooling system
- Low noise operation
- Timing function for maximum guest comfort
- SLEEP-mode function for silence period
- FAST-cool function for immediate cooling
- Adjustable shelves, also in door
- Reversible solid door
- LED interior light
- Integrated handle
- Lock

Minibar cooler with low energy consumption

The TM-C range of hotel minibars from TEFCOLD provides an innovative alternative to the traditional "absorption" refrigeration systems of many minibars. The TM-C model feature a compressor refrigeration system that significantly reduces consumption while providing faster cooling of produce. The units runs at a quiet 38dB and using smart programming can be set to function during periods of the day when the room is likely to be unoccupied (for example between 11am and 4pm). There is also a one press silent function that will sleep the compressor for 1 hour, and a one press function to run the refrigeration system for 5 hours when it is restocked to pull down temperature of the product inside. This range comes in a number of sizes including a drawer version. They are suitable for hotel rooms and boardrooms.

Measures and Content

Temperature Range	°C	+5 to +10
Climate Class		4
Net Volume	l	24
Gross Volume	l	27
Gross / Net Volume	l	27 / 24
Gross / Net Weight	kg	20.5 / 19.5

Design and Material

Door Number & Type		1 hinged solid door
No. of Doors		1
No. of Shelves	pcs	1
Shelves Number & Type		1 plastic shelf
Feet / Legs		Adjustable Feet
Interior Light		LED
Lock		Yes
Exterior Finish		Black
Interior Finish		White

Cooling and Functions


Type of Controller		Electronic
Type of Cooling		Static
Type of Defrost		Automatic
Refrigerant		R600a
Refrigerant Charge	g	24
Thermometer		No

Power and Consumption

Energy Class		D
Max Ambient		+30°C, 55% RH
Annual Energy Consumption	kWh/year	55
Energy Consumption	kWh/24h	0.15
EEl	%	72
Power		13 Amp
Input Power	W	65
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	38

Dimensions

External Dimension (WxDxH)	mm	402 x 440 x 510
Internal Dimension (WxDxH)	mm	310 x 207 x 397
Packed Dimension (WxDxH)	mm	450 x 475 x 550
40ft Container Load	pcs	375



Display with a button for each feature



Integrated handle