TEFCOLD®
COOL PRODUCTS WORLDWIDE



Measures and Content		
Gross / Net Weight	kg	96 / 86
Capacity Cooling Coldroom Units	m³	10,1 - 15
Temperature Range	°C	0 to 8
Design and Material		
Exterior Finish		SS430
Cooling and Functions		
Type of Controller		Electronic
Type of Defrost		Automatic, hot gas
Refrigerant		R290
Refrigerant Charge	g	170
Thermometer		Yes
Power and Consumption		
Energy Consumption	kWh/24h	23.4
Annual Energy Consumption	kWh/year	8541
Input Power	W	1320
Voltage / Frequency	V/Hz	220-240/50
Dimensions		
External Dimension (WxDxH)	mm	600 x 960 x 880
Packed Dimension (WxDxH)	mm	790 x 1150 x 1170
40ft Container Load	pcs	60

CRU1015P w/o Panel


Monoblock Cooler Unit (10.1-15m³)

Product Features
- Monoblock cooling unit
- Automatic condensate evaporation
- Ambient temperature up to +43 °C and 65% humidity
- Digital controller and temperature display
- Stainless steel finish
- Fits panels with a thickness of 80-150 mm

Monoblock cooler unit for temperature -2 to +8 °C

Monoblock cooler unit for cold rooms with a volume of 10.1-15m³.

When installing the monoblock, ensure a minimum distance of 30 cm between the condenser fan (or heat exhaust) and the ceiling. Sufficient ventilation at the installation location is recommended.



Monoblock rear – no panel attached



Digital controller