



CRNF1221

Coldroom (Freezing)

Product Features

- Plug-In ready after assembly
- Many customisation possibilities
- Easy access to products
- Freezing unit
- Easy assembly
- 120 mm panel insulation
- Anti-slip floor in SS304 stainless steel
- Alarm kit as accessory
- Shelves available as accessory
- Ramp available as accessory for easy access

| Measures and Content | | |
|----------------------------|----------|-------------------------|
| Internal Volume | m³ | 3.5 |
| Wall Thickness | mm | 120 |
| Insulation Density | kg/m³ | 42 |
| Temperature Range | °C | -20 to -10 |
| Climate Class | | 5 |
| Gross / Net Weight | kg | 430 / 400 |
| Gross / Net Volume | I | |
| Design and Material | | |
| Door Number & Type | 1 hinged | solid door W:580 H:1765 |
| Max Load on Floor | kg/m² | 2000 |
| Exterior Finish | | White |
| Interior Finish | | White |
| Interior Light | | LED |
| Lock | | Yes |
| Cooling and Functions | | |
| Type of Controller | | Electronic |
| Type of Cooling | | Ventilated |
| Type of Defrost | | Automatic, hot gas |
| Refrigerant | | R290 |
| Refrigerant Charge | g | 150 |
| Thermometer | | Yes |
| Power and Consumption | | |
| Energy Consumption | kWh/24h | 22.49 |
| Annual Energy Consumption | kWh/year | 8208 |
| Input Power | W | 1100 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 60 |
| Dimensions | | |
| Internal Dimension (WxDxH) | mm | 960 x 1860 x 1960 |
| External Dimension (WxDxH) | mm | 1200 x 2100 x 2200 |
| Packed Dimension (WxDxH) | mm | 2200 x 1320 x 2400 |
| 40ft Container Load | pcs | 14 |





Strong handle

Shelf as accessory