TEFCOLD®
COOL PRODUCTS WORLDWIDE



| Measures and Content | | |
|---|---|---|
| Gross / Net Weight | kg | 110 / 100 |
| Capacity Cooling Coldroom Units | m³ | 15,1 - 20 |
| Temperature Range | °C | 0 to 8 |
| **Design and Material** | | |
| Exterior Finish | | SS430 |
| **Cooling and Functions** | | |
| Type of Controller | | Electronic |
| Type of Defrost | | Automatic, hot gas |
| Refrigerant | | R290 |
| Refrigerant Charge | g | 200 |
| Thermometer | | Yes |
| **Power and Consumption** | | |
| Energy Consumption | kWh/24h | 25.92 |
| Annual Energy Consumption | kWh/year | 9461 |
| Input Power | W | 1390 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| **Dimensions** | | |
| External Dimension (WxDxH) | mm | 600 x 960 x 880 |
| Packed Dimension (WxDxH) | mm | 790 x 1150 x 1170 |
| 40ft Container Load | pcs | 60 |

# CRU1520P w/o Panel


## Monoblock Cooler Unit (15.1-20m³)

**Product Features**
- Monoblock cooling unit
- Automatic condensate evaporation
- Ambient temperature up to +43 °C and 65% humidity
- Digital controller and temperature display
- Stainless steel finish
- Fits panels with a thickness of 80-150 mm

## Monoblock cooler unit for temperature -2 to +8 °C

Monoblock cooler unit for cold rooms with a volume of 15,1-20m³.

When installing the monoblock, ensure a minimum distance of 30 cm between the condenser fan (or heat exhaust) and the ceiling. Sufficient ventilation at the installation location is recommended.



Monoblock rear – no panel attached




Digital controller