



PC1250B

Multideck With Doors

Product Features

- Frameless glass doors for great product visibility
- Low energy consumption
- Black interior and exterior
- Adjustable shelves (can be tilted)
- LED light under each shelf
- Ventilated cooling for fast pull-down and even temperature
- Digital controller and temperature display
- Glass end walls as standard
- Castors and locking feet
- 33 mm ticket strips with shelf risers included

Full Glass Door Multideck

The TEFCOLD PC-B range of multidecks is where efficient cooling meets affordability. Featuring a low base together with 5 adjustable shelves, the unit maximises display space allowing you to offer a wide range of produce. Undershelf LED lighting, together with an LED light in the canopy illuminating the top shelf, ensure food and drink is displayed clearly. Self-closing double-glazed frameless glass doors give the best view of produce and help to maintain the cabinet temperature while minimising energy consumption and running costs. All sizes have an energy rating of B. The cabinet is 3M1 specification so can be set for display of packed fresh meat if required. It is also ideal for use with dairy produce, sandwiches, drinks and more, making the PC range suitable for convenience stores, off-licences, cafes and coffee shops.

Measures and Content

Total Display Area	m ²	3.14
Temperature Range	°C	-1 to +5
Climate Class		3
Net Volume	l	764
Gross Volume	l	1292
Gross / Net Volume	l	1292 / 764
Gross / Net Weight	kg	300 / 260

Design and Material

Door Number & Type	2 hinged glass doors	
Tempered glass		Yes
No. of Doors		2
Max load on Shelves	kg/m ²	160
No. of Shelves	pcs	5
Shelf Color		Black
Shelves Number & Type		5 adjustable
Feet / Legs		4 adjustable feet
Castors		4 castors
Interior Light		LED
Exterior Finish		Black RAL9005
Interior Finish		Black (RAL9005)

Cooling and Functions


Type of Controller		Electronic
Type of Defrost		Automatic
Refrigerant		R290
Refrigerant Charge	g	149
Thermometer		Yes

Power and Consumption

Energy Class		B
Max Ambient		+25°C, 60% RH
Annual Energy Consumption	kWh/year	2143
Energy Consumption	kWh/24h	5.87
EEL	%	12.3
Power		13 Amp
Input Power	W	550
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	62

Dimensions

External Dimension (WxDxH)	mm	1310 x 740 x 2050
Internal Dimension (WxDxH)	mm	1250 x 450 x 1540
Packed Dimension (WxDxH)	mm	1360 x 762 x 2256
40ft Container Load	pcs	25



Display with a button for LED light under each shelf

each feature