



FSC891H Black

Black 2-door display cooler with canopy

Product Features

- Approx. 58% more energy efficient than previous range
- LED illuminated canopy
- Internal vertical LED light
- Black interior and exterior
- Adjustable shelves
- Ventilated cooling
- Hinged alu-framed glass doors
- Adjustable feet with rollers to rear
- Digital temperature display

Black 2-door display cooler with canopy

The FSC range is with a an illuminated canopy. The possibility for customized branding is eye-catching and stimulate impulse sales. The unit keeps beverages cold whilst presenting and promoting the products to their best advantage. It has been updated and now uses in average 58% less energy compared to the previous models from the same range.

This model is with black exterior and interior. The black exterior finish looks great, the black interior makes the content stand out - especially with LED lights perfectly illuminating the content. It is ideal for high-end cafes, delis and patisseries.

It comes with 5 adjustable black wire shelves, 2 self-closing hinged glass doors, 2 vertical full length LED lights inside the door frame and a LED light canopy.

Measures and Content

Gross / Net Weight	kg	166 / 153
Net Volume	l	535
Gross Volume	l	707
Gross / Net Volume	l	707 / 535
Temperature Range	°C	+2 to +10
Climate Class		4

Design and Material

Exterior Finish		Black RAL9005
Interior Finish		Black RAL9005
No. of Doors		2
Door No & Type		2 hinged self-closing glass doors
Door Reversible		No
No. of Shelves	pcs	5
Shelves No & Type		5 wire shelves black
Shelf Color		Black
Shelf Dimensions		794 x 540 mm
Max load on Shelves	kg/m²	196
Feet / Legs		4 adjustable feet

Castors		4 rollers
Lock		Yes
Tempered glass		Yes
Canopy Type		D-Shape
Interior Light		LED

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant		R290
Refrigerant Charge	g	115
Thermometer		Yes

Power and Consumption

Energy Class		C
Energy Consumption	kWh/24h	2.63
Annual Energy Cons.	kWh/year	960
EEl	%	34.7
Power Supply		13 Amp
Input Power	W	410
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	48

Dimensions

External Dimension (WxDxH)	mm	890 x 740 x 1990
Internal Dimension (WxDxH)	mm	810 x 561 x 1556
Packed Dimension (WxDxH)	mm	950 x 840 x 2160
40ft Container Load	pcs	28



Illuminated canopy



Strong handles