



CRNF1224

Coldroom (Freezing)

Product Features

- Plug-In - ready after assembly
- Many customisation possibilities
- Easy access to products
- Freezing unit
- Easy assembly
- 120 mm panel insulation
- Anti-slip floor in SS304 stainless steel
- Ventilated floor kit as accessory
- Strip curtain included
- Alarm kit as accessory
- Shelves available as accessory
- Ramp available as accessory for easy access

Measures and Content

Wall Thickness	mm	120
Internal Volume	m ³	4.06
Temperature Range	°C	-20 to -10
Gross / Net Weight	kg	450 / 420

Design and Material

Door Number & Type	1 hinged solid door W:580 H:1765	
No. of Doors	1	
Max Load on Floor	kg/m ²	2000
Interior Light	LED	
Lock	Yes	
Exterior Finish	White	
Interior Finish	White	

Cooling and Functions

Type of Controller	Electronic	
Type of Defrost	Automatic, hot gas	
Refrigerant	R290	
Refrigerant Charge	g	150
Thermometer	Yes	

Power and Consumption

Annual Energy Consumption	kWh/year	8208
Energy Consumption	kWh/24h	22.49
Power	13 Amp	
Input Power	W	1100
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60

Dimensions

External Dimension (WxDxH)	mm	1200 x 2400 x 2200
Internal Dimension (WxDxH)	mm	960 x 2160 x 1960
Packed Dimension (WxDxH)	mm	2400 x 1320 x 2400
40ft Container Load	pcs	8



Strong handle



Shelf as accessory