




BA21H

Back Bar Cooler

Product Features

- EU Energy Class A
- Approx. 59% more energy efficient than previous BA-range
- Double glazed tempered glass
- Reversible glass door
- Ventilated cooling for fast pull-down and even temperature
- Easy access electronic thermostat
- Adjustable shelves
- LED interior light
- Lock

High-quality hinged door backbar with low energy consu

The BA21H Backbar Cooler is a pinnacle of efficiency for your food and hospitality business. With an EU Energy Class A rating, it surpasses its predecessors by approximately 59% in energy efficiency, ensuring cost savings without compromising performance. Equipped with double-glazed tempered glass and hinged glass doors, this cooler optimises insulation and reduces energy loss while providing easy access. The ventilated cooling system guarantees swift pull-downs and consistent temperatures, preserving the freshness of your inventory. The adjustable shelves, LED interior lighting, and a secure lock offer convenience, visibility, and security in one versatile unit.

With energy-saving features, precision temperature control, and a secure design, this cooler is tailored to meet the demands of busy food and hospitality establishments.

Measures and Content

Gross / Net Weight	kg	70 / 64
Net Volume	l	188
Gross Volume	l	196
Gross / Net Volume	l	196 / 188
Total Display Area	m²	0.52
Temperature Range	°C	+2 to +10
Climate Class		4

Design and Material

Exterior Finish		Black
Interior Finish		Stucco aluminium
No. of Doors		2
Door Number & Type		2 hinged glass doors
Door Reversible		No
No. of Shelves	pcs	4
Shelves Number & Type		4 wire shelves chrome
Shelf Color		Chrome
Shelf Dimensions		395x328 mm
Feet / Legs		4 adjustable feet
Lock		Yes
Interior Light		LED
Tempered glass		Yes

Cooling and Functions


Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant Charge	g	70
Refrigerant		R600a
Thermometer		Yes

Power and Consumption

Energy Class		A
Annual Energy Consumption	kWh/year	394
Energy Consumption	kWh/24h	1.08
EEl	%	9
Input Power	W	115
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	44

Dimensions

External Dimension (WxDxH)	mm	900 x 545 x 900
Internal Dimension (WxDxH)	mm	810 x 418 x 734
Packed Dimension (WxDxH)	mm	985 x 575 x 970
40ft Container Load	pcs	96



Adjustable wire shelves



Electronic thermostat