



CRNF1821

Coldroom (Freezing)

Product Features

- Plug-In ready after assembly
- Many customisation possibilities
- Easy access to products
- Freezing unit
- Easy assembly
- 120 mm panel insulation
- Anti-slip floor in SS304 stainless steel
- Alarm kit as accessory
- Shelves available as accessory
- Ramp available as accessory for easy access

Measures and Content		
Internal Volume	m³	5.69
Wall Thickness	mm	120
Insulation Density	kg/m³	42
Temperature Range	°C	-20 to -10
Climate Class		5
Gross / Net Weight	kg	655 / 615
Gross / Net Volume	I	
Design and Material		
Door Number & Type	1 hinged	d solid door W:700 H:1765
Max Load on Floor	kg/m²	2000
Exterior Finish		White
Interior Finish		White
Interior Light		LED
Lock		Yes
Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic, hot gas
Refrigerant		R290
Refrigerant Charge	g	150
Thermometer		Yes
Power and Consumption		
Energy Consumption	kWh/24h	27.02
Annual Energy Consumption	kWh/year	9864
Input Power	W	1510
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60
Dimensions		
Internal Dimension (WxDxH)	mm	1560 x 1860 x 1960
External Dimension (WxDxH)	mm	1800 x 2100 x 2200
Packed Dimension (WxDxH)	mm	2150 x 1250 x 2400
40ft Container Load	pcs	12





Strong handle

Shelf as accessory