



RTC880X1

Roll-Through Chiller

Product Features

- Stainless steel exterior and interior
- Access from front and rear
- Suitable for 20-tray trolleys (not included)
- Ventilated cooling
- Digital controller and temperature display
- Automatic defrost
- Climate class 5 for high performance in warm surroundings

Roll-Through Chiller for catering settings

The TEFCOLD RTC Roll-Through Chiller is tailored for professional kitchens. Its 304-grade stainless steel construction ensures durability, while ventilated cooling keeps your prepared dishes fresh and ready to serve. Designed to accommodate 1 x GN2/1, 1 x 600x400mm or 2 x GN1/1 20-tray trolleys (sold separately), it's perfect for bakeries, events, buffets and catering settings.

Its robust design withstands busy kitchen environments, while doors on both sides provide seamless access between the kitchen and serving area. With functionality, durability, and accessibility, it's an indispensable asset for professional culinary establishments.

Measures and Content

| | | |
|--------------------|-------------------|------------|
| Insulation Density | kg/m ³ | 38 |
| Temperature Range | °C | +2 to +10 |
| Climate Class | | 5 |
| Gross / Net Weight | kg | 205 / 168 |
| Gross / Net Volume | l | 1089 / 416 |

Design and Material

| | |
|-----------------------|---------------------|
| Door Number & Type | 2 hinged solid door |
| Shelves Number & Type | |
| Exterior Finish | SS304 |
| Interior Finish | SS304 |
| Interior Light | No |
| Lock | Yes |

Cooling and Functions

| | |
|--------------------|---------------------|
| Type of Cooling | Ventilated |
| Type of Defrost | Automatic-Off Cycle |
| Refrigerant | R290 |
| Refrigerant Charge | g |
| | 105 |

Power and Consumption


| | | |
|---------------------------|----------|------------|
| Energy Consumption | kWh/24h | 4.6 |
| Annual Energy Consumption | kWh/year | 1679 |
| Input Power | W | 330 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 52 |

Dimensions

| | | |
|----------------------------|-----|----------------------|
| Internal Dimension (WxDxH) | mm | 720 x 906 x 1810 |
| External Dimension (WxDxH) | mm | 880 x 1082 x 2201.5 |
| Packed Dimension (WxDxH) | mm | 905 x 1120 x 2350 mm |
| 40ft Container Load | pcs | 24 |



Digital controller



Lock