



## BA31S-3

### Backbar Cooler

#### Product Features

- EU Energy Class B
- Approx. 59% more energy efficient than previous BA-range
- Double glazed tempered glass
- Energy saving variable speed compressor
- Self-closing sliding glass doors
- Ventilated cooling for fast pull-down and even temperature
- Easy access electronic thermostat
- Adjustable shelves (split level)
- LED interior light
- Lock

### High-quality backbar with low energy consumption

The BA is our range of premium backbars. It has been updated and now uses in average 59% less energy compared to the previous models from the same range. This backbar has ventilated cooling for a short pull-down time to ensure that you can keep up with customer demand for cold beverages. If you need to adjust the temperature this is easily done on the electronic thermostat.

The backbar cooler is made of solid materials and has adjustable chrome shelves with closely-spaced wires, which gives you a high capacity and stability. Furthermore, it has self-closing aluminium sliding doors with double glazed tempered glass. This helps save energy, but it also means a great product visibility.

The BA range is also available in a variant with hinged doors.

#### Measures and Content

Total Display Area	m <sup>2</sup>	0.84
Temperature Range	°C	+2 to +10
Climate Class		4
Gross / Net Weight	kg	101 / 94
Gross / Net Volume	l	311 / 288

#### Design and Material

Door Number & Type	3 sliding glass doors
Door Reversible	No
Tempered glass	Yes
Shelves Number & Type	6 wire shelves chrome
Shelf Color	Chrome
Shelf Dimensions	400x318 / 432x318 mm
Feet / Legs	4 adjustable feet
Exterior Finish	Black
Interior Finish	Stucco aluminium
Interior Light	LED
Lock	Yes

#### Cooling and Functions

Type of Controller	Electronic
Type of Cooling	Ventilated
Type of Defrost	Automatic
Refrigerant	R290
Refrigerant Charge	g90
Thermometer	Yes

#### Power and Consumption

Energy Class		B
Max Ambient		30°C at 55% RH
Energy Consumption	kWh/24h	1.74
Annual Energy Consumption	kWh/year	635
Input Power	W	125
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	44

#### Dimensions

Internal Dimension (WxDxH)	mm	1265 x 418 x 734
External Dimension (WxDxH)	mm	1350 x 515 x 900
Packed Dimension (WxDxH)	mm	1435 x 575 x 970
40ft Container Load	pcs	64



Door holder for loading of the cabinet



Electronic thermostat