TEFCOLD®
COOL PRODUCTS WORLDWIDE



# IC503SD

Ice Cream Freezer

**Product Features**
- Defrost drain
- Flat solid sliding lids
- Static cooling
- Digital temperature display
- Castors, 2 lockable

## Sliding lid chest freezer

This versatile chest freezer with solid sliding lids offers dependable frozen storage for ice cream and a broad selection of other frozen products.

The easy-to-use sliding lids allow fast access to the contents without requiring extra space when opened, making the freezer well suited to busy commercial settings. Designed for a wide variety of frozen foods, this chest freezer provides the flexibility needed for different applications and everyday use.

Its clean and understated exterior allows the freezer to blend in seamlessly to your shop, kiosk, café or foodservice concept, or it can offer generous space for customised branding.

A practical chest freezer for businesses looking for reliable frozen storage, convenient access, flexible use and strong branding opportunities.

| Measures and Content | | |
|---|---|---|
| Gross / Net Weight | kg | 101 / 85 |
| Net Volume | l | 425 |
| Gross Volume | l | 476 |
| Gross / Net Volume | l | 476 / 425 |
| Temperature Range | °C | -23 to -18 |
| Climate Class | | 7 |
| **Design and Material** | | |
| Exterior Finish | | White |
| Interior Finish | | White RAL9010 |
| Number of lids | | 2 |
| Lid Number & Type | | 2 solid sliding lids |
| No. of baskets | pcs | 0 |
| Basket Number & Type | | 0 Wire basket |
| Max No. of Baskets | pcs | 6 |
| Feet / Legs | | |
| Castors | | Castors |
| Lock | | No |
| Interior Light | | No |
| **Cooling and Functions** | | |
| Type of Controller | | Mechanical |
| Type of Cooling | | Static |
| Type of Defrost | | Manual |
| Refrigerant | | R290 |
| Refrigerant Charge | g | 75 |
| Thermometer | | Yes |
| **Power and Consumption** | | |
| Energy Class | | C |
| Max Ambient | | +35°C, 75% RH |
| Energy Consumption | kWh/24h | 1.705 |
| Energy Consumption | kWh/h | 0.071042 |
| Annual Energy Consumption | kWh/year | 622.33 |
| EEI | % | 28.5 |
| Input Power | W | 280 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 48 |
| **Dimensions** | | |
| External Dimension (WxDxH) | mm | 1554 x 635 x 892 |
| Internal Dimension (WxDxH) | mm | 1430 x 510 x 715 |
| Packed Dimension (WxDxH) | mm | 1640 x 750 x 960 |
| 40ft Container Load | pcs | 42 |



Baskets



Castors with and without brake