



UR400X1

Solid Door Refrigerator

Product Features

- Stainless steel exterior
- Integrated handle
- Reversible solid door
- Fan assisted cooling
- Adjustable shelves
- Digital controller and temperature display
- Adjustable feet with rollers to rear
- Lock

Solid door refrigerator, stainless steel

The UR range of solid door refrigerators from TEFCOLD combines traditional reliability with sleek design. Each unit features an integrated handle and adjustable wire shelves holding up to 15 kg each, offering flexible storage. These classic fridges include fan-assisted cooling and a digital thermostat for easy temperature control. Note that this particular model is energy-optimized and the energy consumption is 50% lower than that of its predecessor. Available in various colours and sizes, the UR range offers both solid and glass door models. For freezers, see our UF range.

Measures and Content

| | | |
|--------------------|----|-----------|
| Temperature Range | °C | -2 to +8 |
| Climate Class | | 4 |
| Gross / Net Weight | kg | 82 / 77 |
| Gross / Net Volume | l | 361 / 350 |

Design and Material

| | | |
|-----------------------|-------|----------------------|
| Door Number & Type | | 1 hinged solid door |
| Shelves Number & Type | | 4 wire shelves white |
| Shelf Color | | White |
| Shelf Dimensions | | 503 x 415 mm |
| Max load on Shelves | kg/m² | 110 |
| Feet / Legs | | 2 adjustable feet |
| Castors | | 2 rollers |
| Exterior Finish | | SS430 |
| Interior Finish | | White |
| Interior Light | | No |
| Lock | | Yes |

Cooling and Functions

| | | |
|--------------------|---|---------------------|
| Type of Controller | | Electronic |
| Type of Cooling | | Fan assisted |
| Type of Defrost | | Automatic-Off Cycle |
| Refrigerant | | R600a |
| Refrigerant Charge | g | 70 |

Power and Consumption

| | | |
|---------------------------|----------|------------|
| Energy Class | | A |
| Energy Consumption | kWh/24h | 0.65 |
| Annual Energy Consumption | kWh/year | 237 |
| Input Power | W | 80 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 45 |

Dimensions

| | | |
|----------------------------|-----|------------------|
| Internal Dimension (WxDxH) | mm | 510 x 485 x 1620 |
| External Dimension (WxDxH) | mm | 600 x 615 x 1855 |
| Packed Dimension (WxDxH) | mm | 680 x 680 x 2100 |
| 40ft Container Load | pcs | 51 |



Electronic thermostat



Internal fan