



## CRNF1227

Coldroom (Freezing)

### Product Features

- Plug-In - ready after assembly
- Many customisation possibilities
- Easy access to products
- Freezing unit
- Easy assembly
- 120 mm panel insulation
- Anti-slip floor in SS304 stainless steel
- Alarm kit as accessory
- Shelves available as accessory
- Ramp available as accessory for easy access

Measures and Content		
Internal Volume	$\text{m}^3$	4.63
Wall Thickness	mm	120
Insulation Density	$\text{kg}/\text{m}^3$	42
Temperature Range	°C	-20 to -10
Climate Class		5
Gross / Net Weight	kg	520 / 490
Gross / Net Volume	l	
Design and Material		
Door Number & Type	1 hinged solid door W:580 H:1765	
Max Load on Floor	$\text{kg}/\text{m}^2$	2000
Exterior Finish	White	
Interior Finish	White	
Interior Light	LED	
Lock	Yes	
Cooling and Functions		
Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic, hot gas	
Refrigerant	R290	
Refrigerant Charge	g	150
Thermometer	Yes	
Power and Consumption		
Energy Consumption	$\text{kWh}/24\text{h}$	22.49
Annual Energy Consumption	$\text{kWh}/\text{year}$	8208
Input Power	W	1100
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60
Dimensions		
Internal Dimension (WxDxH)	mm	960 x 2460 x 1960
External Dimension (WxDxH)	mm	1200 x 2700 x 2200
Packed Dimension (WxDxH)	mm	2500 x 1900 x 2400
40ft Container Load	pcs	8



Strong handle



Shelf as accessory