



SGD-240GE

High-end Backbar Cooler

Product Features

- Excellent product visibility
- Suitable for bottles and KEGS
- Low energy consumption
- Adjustable plate shelves
- LED interior light with switch
- Adjustable legs
- Skinplate exterior/interior
- Digital controller and temperature display
- Automatic defrost
- Easy maintenance condenser
- Lock

Spacious backbar cooler with glass doors

The SGD glass door version is built to deliver exceptional style and product presentation combined with superior energy efficiency. This premium cabinet works well for displaying cans and bottles of different shapes and sizes, as the adjustable plate shelves provide a stable, practical surface for easy organization.

Designed with hospitality in mind, the SGD features a sleek anthracite exterior that blends effortlessly into modern, high-end settings. Its coated skinplate interior and exterior are resistant to scratches and visible fingerprints, ensuring it stays looking great even with daily use.

The energy-efficient cooling system ensures a consistent temperature while keeping running costs under control. The temperature can be set easily on the electronic controller and it has automatic defrost for easy maintenance.

Measures and Content

Gross / Net Weight	kg	118 / 105
Net Volume	l	260
Gross Volume	l	282
Gross / Net Volume	l	282 / 260
Temperature Range	°C	+2 to +10
Climate Class		4

Design and Material

Bottom Shelf Dimensions	mm	1042 x 220
Exterior Finish		Anthracite RAL 7021
Interior Finish		Silver
No. of Doors		2
Door Number & Type		2 hinged glass doors
Door Reversible		No
No. of Shelves	pcs	4
Shelves Number & Type		4 adjustable
Shelf Color		Silver
Shelf Dimensions		510 x 355 mm
Max load on Shelves	kg/m²	165
Feet / Legs		Adjustable Feet
Lock		Yes
Interior Light		LED
Tempered glass		No

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant Charge	g	85
Refrigerant		R290
Thermometer		Yes

Power and Consumption

Energy Class		F
Annual Energy Consumption	kWh/year	2577
Energy Consumption	kWh/24h	7.06
EEL	%	67.1
Input Power	W	280
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	47

Dimensions

External Dimension (WxDxH)	mm	1110 x 620 x 840
Internal Dimension (WxDxH)	mm	1040 x 425 x 682
Packed Dimension (WxDxH)	mm	1145 x 640 x 965
40ft Container Load	pcs	76



Adjustable shelves

Digital controller