



1550

LGC7500B

Glass Door Merchandiser

Product Features

- Fully automatic
- Fan assisted cooling
- Automatic defrost
- Lock
- Adjustable shelves
- Castors and locking feet
- LED interior light with switch (2 LED strips per door)
- Digital controller and temperature display
- LED Light canopy with switch
- Internal stainless steel base
- Self closing doors with stay open feature for ease of loading

Elegant display chiller with canopy

The TEFCOLD LGC chiller now available in a sleek black finish. This exciting update allows the unit to seamlessly blend into various retail and catering environments, making it an excellent choice for establishments seeking a sophisticated and high-quality aesthetic. Each door boasts two vertical LED light strips, these draw attention to the product on display giving a striking contrast against the black interior of the cabinet. There is also an LED light canopy which is ideal for branding and advertising. The unit's interior base is manufactured from stainless steel and features curved corners to help with cleaning and hygiene. Additionally, the carefully engineered refrigeration system is highly energy-efficient, minimising operational costs while keeping your products at their optimal temperature. The unit is also fitted with castors, to allow moving for cleaning purposes and other necessary adjustments.

Measures and Content

Gross / Net Weight	kg	245 / 230
Net Volume	l	1436
Gross Volume	l	2050
Gross / Net Volume	l	2050 / 1436
Total Display Area	m ²	2.07
Temperature Range	°C	+1 to +8
Climate Class		4

Design and Material

Exterior Finish		Black RAL9005
Interior Finish		Black
No. of Doors		3
Door Number & Type		3 hinged glass doors
Door Reversible		No
No. of Shelves	pcs	15
Shelves Number & Type		15
Shelf Dimensions		618*622 / 690*622
Max load on Shelves	kg/m ²	196
Tempered glass		Yes
Lock		Yes
Interior Light		LED

Cooling and Functions

Type of Defrost		Automatic / Off Cycle
Refrigerant		R290
Refrigerant Charge	g	150
Thermometer		Yes

Power and Consumption

Energy Class		C
Energy Consumption	kWh/24h	10.6
Annual Energy Consumption	kWh/year	3870
EEL	%	30
Input Power	W	650
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60

Dimensions

External Dimension (WxDxH)	mm	2079 x 805 x 2065
Internal Dimension (WxDxH)	mm	1959 x 640 x 1520
Packed Dimension (WxDxH)	mm	2130 x 860 x 2260
40ft Container Load	pcs	14



Illuminated canopy



Strong castors