



LGC5000B

Glass Door Merchandiser

Product Features

- Fully automatic, ventilated cooling
- LED Light canopy with switch
- Self closing doors with stay open feature for ease of loading
- LED interior light with switch (2 LED strips per door)
- Adjustable shelves
- Digital controller and temperature display
- Internal stainless steel base
- Castors and locking feet
- Automatic defrost

Elegant display chiller with canopy

The TEFCOLD LGC5000 chiller now available in a sleek black finish. This exciting update allows the unit to seamlessly blend into various retail and catering environments, making it an excellent choice for establishments seeking a sophisticated and high-quality aesthetic. Each door boasts two vertical LED light strips, these draw attention to the product on display giving a striking contrast against the black interior of the cabinet. There is also an LED light canopy which is ideal for branding and advertising. The unit's interior base is manufactured from stainless steel and features curved corners to help with cleaning and hygiene. Additionally, the carefully engineered refrigeration system is highly energy-efficient, minimising operational costs while keeping your products at their optimal temperature. The unit is also fitted with castors, to allow moving for cleaning purposes and other necessary adjustments.

Measures and Content

Gross / Net Weight	kg	210 / 190
Net Volume	l	922
Gross Volume	l	1108
Gross / Net Volume	l	1108 / 922
Total Display Area	m ²	1.38
Temperature Range	°C	+1 to +8
Climate Class		4

Design and Material

Exterior Finish		Black
Interior Finish		Black
No. of Doors		2
Door Number & Type		2 hinged glass doors
No. of Shelves	pcs	10
Shelves Number & Type		10
Shelf Dimensions		618*622
Max load on Shelves	kg/m ²	196
Tempered glass		Yes
Lock		Yes
Interior Light		2 x Vertically LED in door frame

Cooling and Functions

Type of Defrost		Automatic / Off Cycle
Refrigerant		R290
Refrigerant Charge	g	120
Thermometer		Yes

Power and Consumption

Energy Class		B
Energy Consumption	kWh/24h	5.21
Annual Energy Consumption	kWh/year	1900
EEl	%	19
Power		13 Amp
Input Power	W	400
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	58

Dimensions

External Dimension (WxDxH)	mm	1382 x 805 x 2065
Internal Dimension (WxDxH)	mm	1262 x 640 x 1520
Packed Dimension (WxDxH)	mm	1430 x 860 x 2260
40ft Container Load	pcs	22



Illuminated canopy



Strong castors