



## Galaxy+ GPL20FGD A

Low-Height Multideck

### Product Features

- Colour is anthracite RAL7016
- Frameless glass doors for great product visibility
- Excellent energy efficiency
- Adjustable shelves (can be tilted)
- Solid 40 mm endwalls with mirrored interior
- LED interior light
- Ventilated cooling
- Can be multiplexed with kit (POA)
- Ticket strip and acrylic front riser as standard

Low-height multideck chiller with doors

The Galaxy+ LOW FGD in colour anthracite RAL7016 offers a highly energy efficient cooling system combined with a gorgeous design. It is a spacious cabinet complete with adjustable shelves and internal LED lighting for optimum product presentation.

The low height of the multidecks allows for creating island installations without blocking the view of the customer. A multiplexing kit is available as accessory, so you can create uninterrupted lines throughout your store.

As a result of a carefully designed refrigeration system and optimal airflow through the chiller, this cabinet has an outstanding low energy consumption and an impressive EU energy rating.

### Measures and Content

Gross / Net Weight	kg	337.6 / 315.6
Net Volume	l	540
Gross Volume	l	1195
Gross / Net Volume	l	1195 / 540
Total Display Area	m <sup>2</sup>	1.92
Temperature Range	°C	-1 to +5
Climate Class		3

### Design and Material

Exterior Finish		Anthracite RAL7016
Interior Finish		Anthracite RAL7016
Door Number & Type		hinged glass doors
Door Reversible		No
No. of Shelves	pcs	3
Shelves Number & Type		3 adjustable
Shelf Color		Anthracite
Shelf Dimensions		938x250/300/350mm
Max load on Shelves	kg/m <sup>2</sup>	160
Feet / Legs		6 adjustable feet
Tempered glass		Yes
Interior Light		LED

### Cooling and Functions

Type of Controller		Electronic
Type of Defrost		Automatic
Refrigerant		R290
Refrigerant Charge	g	145
Thermometer		Yes

### Power and Consumption

Energy Class		B
Max Ambient		+25°C, 60% RH
Energy Consumption	kWh/24h	4.6
Annual Energy Consumption	kWh/year	1679
EEl	%	13.7
Power		16 Amp
Input Power	W	386
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	55

### Dimensions

External Dimension (WxDxH)	mm	1955 x 740 x 1500
Internal Dimension (WxDxH)	mm	1875 x 350 x 1053
Packed Dimension (WxDxH)	mm	2100 x 810 x 2350
40ft Container Load	pcs	14



Digital controller



Strong handles