



SPID150

Serve Over Counter

Product Features

- Excellent product visibility
- Glass structure for protection of food
- Front glass hinges forward if required
- Accepts GN1/1 pan(s) (not supplied)
- Easy access storage compartment
- Black exterior
- Ventilated cooling
- Automatic defrost
- LED interior light

Ventilated serve over counter with gastronorm dimensi

Meet the SPID serve over counter - the ultimate cool solution for your food display needs. This stylish counter has an effective ventilated cooling system, which circulates cool air evenly throughout the cabinet. It is designed to keep your products at the ideal temperature while offering easy access. A visual and functional delight, it's perfect for sandwich shops, delis, and supermarkets to exhibit their offerings enticingly. It has a flat glass structure for good hygiene and the front glass hinges forward for easy cleaning. The serve over counter is suitable for gastronorm pans (not included).

Measures and Content

| | | |
|--------------------|----------------|-----------|
| Total Display Area | m ² | 1.14 |
| Temperature Range | °C | -1 to +5 |
| Climate Class | | 3 |
| Gross / Net Weight | kg | 219 / 184 |
| Gross / Net Volume | l | |

Design and Material

| | | |
|-------------------|--|---------------------|
| Door No & Type | | 2 hinged solid door |
| Tempered glass | | Yes |
| Shelves No & Type | | |
| Feet / Legs | | 4 adjustable feet |
| Exterior Finish | | Black RAL9005 |
| Interior Finish | | White RAL9003 |
| Interior Light | | Yes |
| Lock | | No |

Cooling and Functions

| | | |
|--------------------|---|------------|
| Type of Controller | | Electronic |
| Type of Cooling | | Ventilated |
| Type of Defrost | | Automatic |
| Refrigerant | | R290 |
| Refrigerant Charge | g | 120 |
| Thermometer | | Yes |

Power and Consumption

| | | |
|---------------------|----------|------------|
| Energy Consumption | kWh/24h | 8.8 |
| Annual Energy Cons. | kWh/year | 3212 |
| Input Power | W | 781 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 54 |

Dimensions

| | | |
|----------------------------|-----|--------------------|
| Internal Dimension (WxDxH) | mm | 1440 x 670 x |
| External Dimension (WxDxH) | mm | 1505 x 960 x 1235 |
| Packed Dimension (WxDxH) | mm | 1525 x 1065 x 1230 |
| 40ft Container Load | pcs | 28 |



Designed for GN1/1 pans, not supplied



Thermometer