



IC502SCEB

Sliding Curved Glass Lid Chest Freezer

Product Features

- Sloping display for excellent presentation
- Curved sliding lids with lock
- Includes full set of baskets
- Ideal for branding
- LED interior light
- Digital thermometer
- Castors with brake
- Climate class 5 for high performance in warm surroundings

Sliding Curved Glass Lid Chest Freezer

An excellent choice of sliding glass lid chest freezers, similar to the IC-SC range but with a sloping top for a better visual display and curved lids which always look better. Ideal for display of frozen food including ice cream and lollies. Sturdy heavy duty castors are fitted to enable easy movement of the cabinet, two of the four castors are lockable. Excellent adjustment of the temperature means you can hold a temperature around -14°C, ready to serve ice cream, or down to -24°C for other frozen food. The unit comes with a lock as standard and a defrost drain for easy cleaning. The unit also has a fan assisted condenser for efficient operation. A full set of baskets with dividers supplied as standard. A firm favourite with many ice cream companies. (A glass canopy version for scooping ice cream is also available).

Measures and Content

Gross / Net Weight	kg	85 / 72
Net Volume	l	398
Gross Volume	l	427
Gross / Net Volume	l	427 / 398
Temperature Range	°C	-24 to -14
Climate Class		5

Design and Material

Exterior Finish		White
Interior Finish		White painted steel
Number of lids		2
Lid Number & Type		2 curved sliding temp. glass lids
No. of baskets	pcs	6
Basket Number & Type		6 Wire baskets, white
Max No. of Baskets	pcs	6
Castors		4 wheels, 2 with brake
Lock		Yes
Tempered glass		Yes
Interior Light		LED

Cooling and Functions

Type of Controller		Mechanical
Type of Cooling		Static
Type of Defrost		Manual
Refrigerant		R290
Refrigerant Charge	g	110
Thermometer		Yes

Power and Consumption

Energy Class		D
Max Ambient		+40°C, 40% RH
Energy Consumption	kWh/24h	2.622
Annual Energy Consumption	kWh/year	957.03
EEL	%	43.9
Power		13 Amp
Input Power	W	265
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	45

Dimensions

External Dimension (WxDxH)	mm	1550 x 615 x 949
Internal Dimension (WxDxH)	mm	1420 x 495 x 710
Packed Dimension (WxDxH)	mm	1640 x 750 x 1010
40ft Container Load	pcs	42



Baskets



Lock