



UR200X1

Storage Cooler

Product Features

- Stainless steel exterior
- Integrated handle
- Reversible solid door
- Fan assisted cooling
- Adjustable shelves
- Digital controller and temperature display
- Adjustable feet with rollers to rear
- Lock

Low-energy undercounter storage cooler, stainless steel

The TEFCOLD UR200X1 is a classic undercounter storage cooler with an impressively low energy consumption. In fact, it uses 47% less energy than the standard UR200 models. It comes with adjustable wire shelves with a load capacity of up to 15 kg per shelf. The small storage fridge has fan-assisted cooling, and the temperature is easy to set on a digital thermostat. The UR range is available in various colors and sizes, and you can choose between solid door- or glass door models. See the UF range for freezer options.

Measures and Content

| | | |
|--------------------|----|-----------|
| Temperature Range | °C | -2 to +8 |
| Climate Class | | 4 |
| Gross / Net Weight | kg | 54 / 49 |
| Gross Volume | l | 129 |
| Gross / Net Volume | l | 129 / 119 |

Design and Material

| | | |
|-------------------------|-------------------|----------------------|
| Door No & Type | | 1 hinged solid door |
| Shelves No & Type | | 3 wire shelves white |
| Shelf Color | | White |
| Shelf Dimensions | | 503 x 415 mm |
| Bottom Shelf Dimensions | | 503x225 |
| Max load on Shelves | kg/m ² | 110 |
| Feet / Legs | | 2 adjustable feet |
| Castors | | 2 rollers |
| Exterior Finish | | SS430 |
| Interior Finish | | White |
| Interior Light | | No |
| Lock | | Yes |

Cooling and Functions

| | | |
|--------------------|---|---------------------|
| Type of Controller | | Electronic |
| Type of Cooling | | Fan assisted |
| Type of Defrost | | Automatic-Off Cycle |
| Refrigerant | | R600a |
| Refrigerant Charge | g | 50 |

Power and Consumption

| | | |
|---------------------|----------|----------------|
| Energy Class | | A+ |
| Max Ambient | | 30°C at 55% RH |
| Energy Consumption | kWh/24h | 0.59 |
| Annual Energy Cons. | kWh/year | 215 |
| Power Supply | | 13 Amp |
| Input Power | W | 70 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 45 |

Dimensions

| | | |
|----------------------------|-----|------------------|
| Internal Dimension (WxDxH) | mm | 510 x 485 x 620 |
| External Dimension (WxDxH) | mm | 600 x 615 x 855 |
| Packed Dimension (WxDxH) | mm | 680 x 680 x 1050 |
| 40ft Container Load | pcs | 114 |



Internal fan



Integrated handle