



NIC202SC

Ice Cream Freezer

Product Features

- Flat sliding glass lids with lock
- Great branding possibilities
- LED interior light
- Castors with brake
- Digital thermometer
- Powder coated white steel inner liner
- Includes full set of baskets
- Climate class 5 for high performance in warm surroundings

Elegant chest freezer with flat sliding glass lids

The NIC-SC range is a compact display chest freezer in an elegant design. It has curved corners, rounded edges and flat sliding glass lids.

It is a very stable and solid build, but at the same time on wheels so that it is easy to change location in the shop.

It comes in many sizes, which makes this model perfect for smaller shops and delis with limited space as well as larger shops, gas stations, supermarkets etc.

All sizes are environmental friendly and can be branded for better presentation of the cabinet content.

It is ideal for display of frozen food including ice cream and lollies. Temperature can be held around -14°C for ice cream or around -21°C for other frozen foods.

All sizes have glass lids with a lock for security. They also have a defrost drain for cleaning out the unit.

| Measures and Content | | |
|----------------------------|----------|------------------------|
| Temperature Range | °C | -24 to -14 |
| Climate Class | | 5 |
| Gross / Net Weight | kg | 63 / 52 |
| Gross / Net Volume | l | 186 / 138 |
| Design and Material | | |
| Tempered glass | | Yes |
| Max No. of Baskets | pcs | 2 |
| Castors | | 4 wheels, 2 with brake |
| Exterior Finish | | White |
| Interior Finish | | White painted steel |
| Interior Light | | LED |
| Lock | | Yes |
| Cooling and Functions | | |
| Type of Controller | | Mechanical |
| Type of Cooling | | Static |
| Type of Defrost | | Manual |
| Refrigerant | | R600a |
| Refrigerant Charge | g | 55 |
| Thermometer | | Yes |
| Power and Consumption | | |
| Energy Class | | D |
| Max Ambient | | 40°C at 40% RH |
| Energy Consumption | kWh/24h | 1.206 |
| Annual Energy Consumption | kWh/year | 440.19 |
| EEI | % | 37.8 |
| Power | | 13 Amp |
| Input Power | W | 165 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 45 |
| Dimensions | | |
| Internal Dimension (WxDxH) | mm | 600 x 510 x 576 |
| External Dimension (WxDxH) | mm | 740 x 650 x 885 |
| Packed Dimension (WxDxH) | mm | 810 x 765 x 940 mm |
| 40ft Container Load | pcs | 84 |



White coated steel inner liner



Illuminated display board as option (accessory)