



IDA600-W1+

Scoop Ice Cream Display

Product Features

- Curved glass canopy
- Sliding glass lids
- Storage under baskets
- Ideal for branding
- Internal LED light
- Strong castors
- Static cooling

Static Scoop Ice Cream Freezer

The IDA scoop ice cream freezer provides a spacious, efficient option for showcasing your ice cream selection. Its simple design coupled with mobility on castors makes it an ideal choice for any ice cream shop or retail environment. You can easily enhance its clean design with custom branding to make the unit distinctive and draw attention to your rich variety of flavours. Equipped with a curved glass sneezeguard and internal LED lighting, the freezer ensures excellent product presentation. Meanwhile sliding lids help conserve energy during non-serving times. Specifically designed for efficiency, this static scoop ice cream freezer is optimised to accommodate baskets suitable for 5-litre plastic tubs, with an additional storage space underneath. These baskets are available as accessories, but note they are intended solely for 5-litre plastic tubs. If you need baskets for Napoli pans or perhaps wish to use the freezer for other frozen foods, other types of baskets are also available as options. Baskets are not included, but are available as accessories.

The IDA range was previously named ISOA - nothing has changed except for the naming.

Measures and Content

Total Display Area	m ²	1.72
Serving Capacity		14 Plastic Tubs (5 L)
		14 Plastic Tubs (5L) + 2 Plastic Tubs (2.5L)
Storage capacity (under)		36 Plastic Tubs (5L)
		36 Plastic Tubs (5L)
Temperature Range	°C	-23 to -16
Climate Class		7
Gross / Net Weight	kg	133 / 126

Design and Material

Tempered glass		Yes
Castors		Wheels
Interior Light		LED
Lock		No
Exterior Finish		White RAL9010
Interior Finish		White RAL9010

Cooling and Functions


Type of Controller		Mechanical
Type of Cooling		Static
Type of Defrost		Manual
Refrigerant		R290
Refrigerant Charge	g	112
Thermometer		Yes

Power and Consumption

Energy Class		D
Max Ambient		35°C at 75% RH
Annual Energy Consumption	kWh/year	990
Energy Consumption	kWh/24h	2.71
EEl	%	39.6
Input Power	W	241
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	49

Dimensions

External Dimension (WxDxH)	mm	1804 x 694 x 1330
Packed Dimension (WxDxH)	mm	1860 x 760 x 920
40ft Container Load	pcs	28



Scooping basket option



Curved glass for nice presentation