

## CRPF1530

### Coldroom (Cooling)

#### Product Features

- Plug-In - ready after assembly
- Many customisation possibilities
- Easy access to products
- Easy assembly
- Anti-slip floor in SS304 stainless steel
- 80 mm panel insulation
- Shelves available as accessory
- Ramp available as accessory for easy access

#### Measures and Content

Internal Volume	m³	7.76
Wall Thickness	mm	80
Insulation Density	kg/m³	42
Temperature Range	°C	0 to +8
Climate Class		5
Gross / Net Weight	kg	352 / 322
Gross / Net Volume	l	

#### Design and Material

Door Number & Type	1 hinged solid door W:700 H:1845	
Max Load on Floor	kg/m²	1500
Exterior Finish	White	
Interior Finish	White	
Interior Light	LED	
Lock	Yes	

#### Cooling and Functions

Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic, hot gas	
Refrigerant	R290	
Refrigerant Charge	g	150
Thermometer	Yes	

#### Power and Consumption


Energy Consumption	kWh/24h	21.12
Annual Energy Consumption	kWh/year	7709
Input Power	W	905
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60

#### Dimensions

Internal Dimension (WxDxH)	mm	1340 x 2840 x 2040
External Dimension (WxDxH)	mm	1500 x 3000 x 2200
Packed Dimension (WxDxH)	mm	2200 x 1900 x 2400
40ft Container Load	pcs	10



Strong handle



Shelf as accessory