



HD690

Glass Door Merchandiser

Product Features

- High efficiency compressor and EC fans
- Low E glass door equivalent to triple glazing
- Fully automatic
- Fan assisted cooling
- Adjustable shelves (split level)
- Adjustable feet
- LED interior light with switch
- Thermometer
- LED Light canopy with switch
- · Replaceable door gasket

The Staycold range of glass door merchandisers is made in South Africa and are designed to cope with their hot and often humid environment, their units are able to work in a scorching ambient of up to 40°C. This combined with an excellent build quality has gained them a reputation in the UK for long lasting units that keep produce at the right temperature, especially during the warmer months. Use of high efficiency compressor, Danfoss intelligent controller, Low E glass (better insulation), LED lighting, EC energy efficient fans on evaporator and condenser all add up to a great energy saving package and low running costs in a premium cabinet.

| Measures and Content | | |
|----------------------------|----------|---------------------|
| Temperature Range | °C | +1 to +10 |
| Climate Class | | 5 |
| Gross / Net Weight | kg | 119 / 117 |
| Gross / Net Volume | I | 525 / |
| Design and Material | | |
| Door Number & Type | | 1 hinged glass door |
| Door Reversible | | No |
| Shelves Number & Type | | 4 |
| Max load on Shelves | kg/m² | 196 |
| Exterior Finish | | White |
| Interior Finish | | White |
| Interior Light | | LED |
| Cooling and Functions | | |
| Type of Defrost | | Off Cycle |
| Refrigerant | | R290 |
| Refrigerant Charge | g | 140 |
| Thermometer | | Yes |
| Power and Consumption | | |
| Energy Class | | E |
| Energy Consumption | kWh/24h | 3.3 |
| Annual Energy Consumption | kWh/year | 1205 |
| Power | | 13 Amp |
| Max Ambient | | 40°C at 40% RH |
| Input Power | W | 452 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 57 |
| Dimensions | | |
| Internal Dimension (WxDxH) | mm | 600 x 550 x 1380 |
| External Dimension (WxDxH) | mm | 690 x 635 x 2020 |
| Packed Dimension (WxDxH) | mm | 685 x 650 x 2110 |
| 40ft Container Load | pcs | 54 |
| | | |

