



EXTRA1250CD

Supermarket Multideck Cooler

Product Features

- Can be multiplexed - Create uninterrupted continuous line
- Temperature Class 3M1
- Heavy duty shelving with strengthening bar
- Adjustable extra deep shelves to maximise capacity
- Tilting function for better product display
- Internal vertical LED light
- Base plus 4 shelves
- Glass end walls as standard
- Multiplexing kit as accessory

Full Glass Door Multideck Cooler with Multiplexing Option

EXTRA Multideck is a full glass door quality cooler with double glazed hinged glass doors for added energy efficiency savings on running costs. For greater stock capacity it has 460mm deep shelves to help maximise sales during busy periods and reduce restocking. It has excellent internal illumination with vertical LED lighting in each door and horizontally across the top on the 2500 model. Shelves can be flat or tilted to 10 or 20 degrees with ticket strips and shelf risers as standard. It is suitable for display of packed fresh meat, dairy or drinks and is ideal for supermarkets, convenience stores, delis and sandwich shops where plug-in refrigeration is required. Installation is simple and quick. No special requirements as refrigerant charge is below 150g. The model allows for multiplexing and increases your possibilities to make the most of the space, you have available. The unit can be ordered without end walls and with a multiplexing kit if required.

Measures and Content

Total Display Area	m ²	1.81
Temperature Range	°C	+2 to +6
Climate Class		3
Gross / Net Weight	kg	340 / 320
Gross / Net Volume	l	880 / 770

Design and Material

Door No & Type	2 hinged glass doors	
Tempered glass	Yes	
Door Reversible	No	
Shelves No & Type	4 black sheet, tilting + base	
Shelf Color	Black	
Max load on Shelves	kg/m ²	100
Feet / Legs	4 adjustable feet	
Castors	Option	
Exterior Finish	Black / Glass	
Interior Finish	Black	
Interior Light	2 x Vertically LED	
Lock	No	

Cooling and Functions

Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic, hot gas	
Refrigerant	R290	
Refrigerant Charge	g	144
Thermometer	Yes	

Power and Consumption

Energy Class	D	
Energy Consumption	kWh/24h	11
Annual Energy Cons.	kWh/year	4015
Input Power	W	1100
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	53

Dimensions

Internal Dimension (WxDxH)	mm	1250 x 610 x 1399
External Dimension (WxDxH)	mm	1350 x 920 x 2035
Packed Dimension (WxDxH)	mm	1450 x 975 x 2230
40ft Container Load	pcs	16



Glass end walls as standard



60x40 cm boxes fit perfectly