



## SOCA45EXTB

Serve Over Counter

### Product Features

- Excellent product visibility
- Black finish
- Glass front lifts up for easy cleaning
- Temperature Class 3M1
- Ventilated cooling
- Anti mist front glass
- LED top light
- Stainless steel bumper bars
- Stainless steel rear shelf
- Can be multiplexed with kit (POA)

45° corner module for serve over counter

This SOCA corner module is designed to create complete counter solutions in combination with additional serve over counters from the same range. If you want to opt for a 90° rounded corner, you can combine two of these 45° corner modules. This specific model has the wide side visible to the customer whilst being more narrow on the staff side. We also offer a model which has the opposite dimensions, so you can set things up depending on the way you'd like your counter to turn. To maximise your space and customer experience. This high-quality serve over counter offers a sleek design and features anti-mist glass, LED top lighting, and a spacious stainless steel deck that stays chilled, thanks to ventilated cooling and airholes on the rear of the deck. It's ideal for butcher shops and delis looking for gorgeous display space. In addition to its good looks, it's also practical and easy to clean with a stainless steel interior and front glass that lift upwards and stays in place while cleaning. Be aware that if the corner module is installed along with another SOC counter, you cannot open the front glass on both units at the same time or you risk ruining the glass.

### Measures and Content

Total Display Area	m²	0.88
Temperature Range	°C	0 to +4
Climate Class		3
Gross / Net Weight	kg	200 / 160
Gross / Net Volume	l	90

### Design and Material

Door Number & Type	
Tempered glass	Yes
Shelves Number & Type	
Feet / Legs	Adjustable Feet
Interior Light	LED
Lock	No

### Cooling and Functions

Type of Controller	Electronic
Type of Cooling	Ventilated
Type of Defrost	Electric
Refrigerant	R290
Refrigerant Charge	g130
Thermometer	Yes

### Power and Consumption

Max Ambient		25°C at 60% RH
Input Power	W	610
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60

### Dimensions

Internal Dimension (WxDxH)	mm	900 x
External Dimension (WxDxH)	mm	x 1120 x 1190
Packed Dimension (WxDxH)	mm	1400 x 1250 x 1400
40ft Container Load	pcs	8



Digital controller



Bumper bars